


## CP0611 GASED - The "Reference" in 1" impact: Compact, Comfortable & Extremely Durable

## **Benefits**



- Operator comfort and control thanks to perfect ergotnomic design even at VERY high torque
- "Constant & progressive" torque thanks to the 2-Jaw clutch
- Unmatched durability with reliable mechanism & durable housing
- Ideal for Heavy Industrial Maintenance and Production applications



## **Features**

- Super Industrial 1" impact wrench
- Reliable 2-jaw clutch with the highest Blows per Minutes
- Full Teasing (outside) trigger with durable reverse Durable aluminum body & indestructible steel clutch housing
- Compact 3-part construction & easy maintenance
- Hole type socket retainer with o-Ring
- 360° adjustable D-type side handle

| Technical description      |                          |                |
|----------------------------|--------------------------|----------------|
| Part number                | T022580                  |                |
| Model                      | CP0611 GASED             |                |
| Joint type: soft           | yes                      |                |
| Joint type: hard           | yes                      |                |
| Handle type                | D-Handle Outside Trigger |                |
| Square drive               | 1"                       |                |
| Working Torque Range (fwd) | 1,220-2,440 Nm           | 900-1,800      |
| Maximum Torque (fwd)       | 3790 Nm                  | 2800 ft.lbs    |
| Maximum Torque (reverse)   | 3790 Nm                  | 2800 ft.lbs    |
| Free speed                 | 3500 rpm                 |                |
| Blows per minute           | 1020                     |                |
| Net weight                 | 10.2 kg                  | 22.5 lb        |
| Power/weight ratio         | 371.6 Nm/kg              | 124.4 ft.lb/lb |
| Length                     | 318 mm                   | 12.52"         |
| Side to center             | 46 mm                    | 1.81"          |
| Actual air consumption     | 22.6 l/s                 | 48 cfm         |
| Air inlet thread size      | 0.5 "                    |                |
| Noise level                | 97 db(A)                 |                |
| Sound Power                | 108 db(A)                |                |
| Vibration (ISO-8662-7)     | 10.9 m/s <sup>2</sup>    |                |
| Vibration α (ISO-28927-2)  | 16.1 m/s²                |                |
| Vibration K (ISO-28927-2)  | 4.5 m/s <sup>2</sup>     |                |
| Socket retainer            | Hole                     |                |
| Clutch type                | 2-jaw clutch             |                |
| Bolt size                  | M36                      |                |