

Benefits

- ▶ Great power for general maintenance applications
- ▶ Reinforced clutch mechanism
- ▶ Low vibration for a better operator confort

Features

- ▶ 1" D-handle impact wrench with dual retainer (Hole + Ring)
- ▶ Pinless closed reinforced rocking dog impact mechanism
- ▶ ergonomic side handle
- ▶ Integrated protective cover on the clutch housing
- ▶ Full teasing trigger
- ▶ Regulator with integrated forward/reverse with 3-position power settings in both directions



Technical description		
Part number	8941077820	
Model	CP7782	
Over carton	670*245*130	26,35*9,6*5,11
Handle type	D-Handle Inside Trigger	
Square drive	1"	
Working Torque Range (fwd)	500 - 2000 Nm	370 - 1475
Maximum Torque (reverse)	2600 Nm	1920 ft.lbs
Free speed	5200 rpm	
Blows per minute	500	
Net weight	10.1 kg	22.2 lb
Power/weight ratio	257.4 Nm/kg	86.5 ft.lb/lb
Length	370 mm	14.7"
Average air consumption	4.8 l/s	10 cfm
Actual air consumption	19.2 l/s	40.7 cfm
Air inlet thread size	0.5 "	
Min. hose size	13 mm	1/2"
Noise level	100 db(A)	
Sound Power	111 db(A)	
Vibration α (ISO-28927-2)	7.8 m/s ²	
Vibration K (ISO-28927-2)	1.8 m/s ²	
Socket retainer	Dual (hole+friction)	
Clutch type	Pin less closed rocking dog	
Bolt size	M32	
Box dimensions	670*245*130	26,35*9,6*5,11