



Benefits

- ▶ Enlarge applications coverage
- ▶ Durable, reliable and easy to service
- ▶ Maximize operator comfort

Features

- ▶ Air riveters
- ▶ for General Maintenance or Light-duty Production
- ▶ Compact size and composite body
- ▶ 1/4" (6.4 mm) max. capacity
- ▶ Heavy pulling: up to 3,530 lbs (1.6 T)
- ▶ Low vibrations and low noise level
- ▶ Includes: 3/16", 1/4", 1/4" monobolt (4.8, 6.4, and 6.4 mm monobolt) nose pieces
- ▶ Jaw, syringe, service wrenches and oil bottle

Technical description		
Part number	8941098840	
Model	CP9884	
Max axial pulling load	1600 kg	3530 lb
Net weight	1.9 kg	4.2 lb
Length	310 mm	12.2"
Average air consumption	1.05 l/s	2 1/4 cfm
Actual air consumption	4.3 l/s	9 cfm
Actual air consumption	258 l/mn	9 cfm
Air inlet thread size	0.25 "	
Min. hose size	10 mm	3/8"
Noise level	56 db(A)	
Sound DBA pressure	67 db(A)	
Vibration (ISO-8662-12)	<2.5 m/s²	
Vibration α (ISO-28927-8)	<2.5 m/s²	