





## **Benefits**

- Extended Length & Compact Gear Housing
- Comfort
- Easy to Use
- Safety & Convenient
- Powerful
- Durable
- Ideal for cutting composite, metal, bolts, ... especially in tight spaces

## **Features**

- ▶ 4" = 100 mm for better reach and easy access to restricted areas
- Composite grip to reduce cold air transmission to operators
- Spindle lock system for easier wheel changing
- ▶ 11 position adjustable swivel guard 126° adjustable for better operator protection & greater visibility of cutting operations
- Safety throttle lever to prevent accidental start up
- Rear exhaust
- 1 HP motor & 14000 rpm
- High quality steel for internal gears
- Cutting disc size : 4" / 100 mm (1/16" X 3/8") (1/8" X 3/8")
- 360° swivel air inlet

| Technical description     |            |        |
|---------------------------|------------|--------|
| Part number               | 8941091161 |        |
| Model                     | CP9116     |        |
| Max. speed                | 14000 rpm  |        |
| Free speed                | 14000 rpm  |        |
| Power                     | 746 W      |        |
| Net weight                | 1.8 kg     | 3.7 lb |
| Length                    | 370 mm     | 14.75" |
| Chuck / wheel size        | 100 mm     | 4"     |
| Average air consumption   | 1.9 l/s    | 4 cfm  |
| Actual air consumption    | 1.9 l/s    | 4 cfm  |
| Air inlet thread size     | 0.25 "     |        |
| Min. hose size            | 10 mm      | 3/8"   |
| Noise level               | 86 db(A)   |        |
| Sound DBA pressure        | 97 db(A)   |        |
| Vibration (ISO-8662-12)   | 3 m/s²     |        |
| Vibration α (ISO-28927-8) | 3 m/s²     |        |
| Vibration K (ISO-28927-8) | 3 m/s²     |        |