

CP3119-22 - High performance



Benefits

- ▶ Industrial
- ▶ High productivity
- ▶ Highest durability in demanding applications up to 2000 hours maintenance intervals

Features

- ▶ Steel housing
- ▶ Insulating composite over-housing
- ▶ Streamlined safety lever
- ▶ Rear exhaust
- ▶ 1/4" (6.35 mm) collet holder
- ▶ 1.2 hp (900 W) governed motor
- ▶ 22,000 rpm free speed

Technical description		
Part number	6151600080	
Model	CP3119-22	
Collet size	6.35 mm	1/4"
Free speed	22000 rpm	
Power	900 W	1.2 hp
Rear exhaust	Rear exhaust	
Length	222 mm	8.8"
Net weight	1 kg	2.2 lb
Noise level	81 db(A)	
Sound Power	92 db(A)	
Vibration (ISO-8662-13)	NA m/s ²	
Vibration α (ISO-28927-12)	<2.5 m/s ²	
Average air consumption	13 l/s	19.08 cfm
Average air consumption	780 l/mn	19.08 cfm
Actual air consumption	18 l/s	38.16 cfm
Actual air consumption	1080 l/mn	38.16 cfm
Free speed air consumption	13 l/s	28 cfm

Min. hose size	10 mm	3/8"
Air inlet thread size	0.375 "	
Box dimensions	353X173x63	