



Benefits

- ▶ Torque limited in forward: 60/70 ft. Lbs. - 90/100 Nm
- ▶ Full power in reverse
- ▶ One Hand Operation: 2 power setting positions
- ▶ Insulation & Comfort: Contoured comfort grip handle instead of TPR injected in handle
- ▶ Low sound level
- ▶ Suited for all light vehicle tire changing applications

Features

- ▶ 1/2" composite impact wrench with friction ring socket retainer
- ▶ 2 setting positions : one in Reverse and one Torque Limited in forward
- ▶ 60/70 ft. lbs. - 90/100 Nm in torque limited position in forward
- ▶ 920 ft.lbs - 1,250Nm of maximum torque in reverse
- ▶ Aluminum clutch & rear housings
- ▶ Thermo-plastic rubber injected in housing - Resistant to most chemicals used in workshops
- ▶ Universal & durable twin hammer mechanism
- ▶ Full teasing trigger
- ▶ 360° swivel air inlet
- ▶ The CP7748TL series is intended to be used as a "snugging" tool prior to final tightening with a calibrated torque wrench to reach the car manufacturer's specified torque rating for wheel assembly.
- ▶ Torque results vary greatly depending on the type of wheel, air pressure, run time and many other factors.

| Technical description | | |
|----------------------------------|----------------------|----------------|
| Part number | 8941077484 | |
| Model | CP7748TL | |
| Over carton | 455*230*418 | 17.9*9.1*16.5 |
| Handle type | Pistol | |
| Square drive | 1/2" | |
| Working Torque Range (fwd) | 90-96 Nm | 66-70 |
| Maximum Torque (reverse) | 1250 Nm | 922 ft.lbs |
| Free speed | 8200 rpm | |
| Blows per minute | 850 | |
| Net weight | 2.2 kg | 4.8 lb |
| Power/weight ratio | 568.2 Nm/kg | 192.1 ft.lb/lb |
| Length | 200 mm | 7.8" |
| Side to center | 38 mm | 1 1/2" |
| Average air consumption | 2.5 l/s | 5 1/2 cfm |
| Actual air consumption | 10 l/s | 22 cfm |
| Air inlet thread size | 0.25 " | |
| Min. hose size | 10 mm | 3/8" |
| Noise level | 86 db(A) | |
| Sound Power | 97 db(A) | |
| Vibration α (ISO-28927-2) | 4.8 m/s ² | |
| Vibration K (ISO-28927-2) | 1.5 m/s ² | |
| Socket retainer | Friction ring | |
| Clutch type | Twin Hammer | |
| Box dimensions | 210*206*75 | 8.3*2.1*3 |