



Benefits

- ▶ Great Performance
- ▶ Lightweight
- ▶ Comfort
- ▶ Easy to Use
- ▶ Rugged and Robust
- ▶ Easy Operation

Features

- ▶ 14.5 lbs. – 6.6 kg
- ▶ 1300 ft.lbs. / 1760 Nm in reverse
- ▶ Twin hammer mechanism
- ▶ Steel motor
- ▶ Intuitive Forward / Reverse lever & power regulator on both sides
- ▶ 4 position power settings on both sides
- ▶ Side handle with soft touch grip
- ▶ Down exhaust
- ▶ Aluminum housing
- ▶ Composite cover on the clutch housing
- ▶ Socket retainer ring

Technical description		
Part number	8941077731	
Model	CP7773D	
Over carton	350*210*290	13,8*8,3*11,4
Handle type	D-Handle Inside Trigger	
Square drive	1"	
Working Torque Range (fwd)	340-1450 Nm	250-1070
Maximum Torque (reverse)	1760 Nm	1300 ft.lbs
Free speed	6600 rpm	
Net weight	6.6 kg	14.5 lb
Length	290 mm	11.4"
Side to center	45 mm	1.8"
Actual air consumption	19.3 l/s	41 cfm
Free speed air consumption	26.8 l/s	
Air inlet thread size	0.5 "	
Min. hose size	13 mm	3/8"
Noise level	98 db(A)	
Sound Power	109 db(A)	
Vibration α (ISO-28927-2)	12 m/s²	
Vibration K (ISO-28927-2)	3.3 m/s²	
Socket retainer	Friction ring	
Clutch type	Twin hammer	
Box dimensions	325*190*130	12,8*7,5*5,1