## **Chicago Pneumatic**



# SIZE MATTERS New Ultra Compact Tool



Vehicle Service

People. Passion. Performance.



### **CP7732C**

1/2" Stubby Impact Wrench



4-1/4 IN. - 108 MM ONLY

### **POWERFUL**

460 ft.lbs - 625 Nm of maximum torque in reverse

### **HIGH DURABILITY & ROBUST**

- Jumbo hammer mechanism
- Steel motor
- Aluminum clutch housing

### **COMFORT & LIGHTWEIGHT**

- Composite housing
- Curved handle with Thermo-Plastic Rubber injected housing, for a durable and comfortable grip



CONVENIENT

Socket retainer ring

### **EASY OPERATION**

- S2S "Side-to-side": 1 handed Forward Reverse operation
- New power setting system:
   1 handed-operation behind the trigger
   2 positions in reverse:
  - maximum and low torque
  - 2 positions in forward: maximum and low torque



Full teasing trigger



### **DIMENSIONS**

ļ	7	E	3	С				
in.	mm	in.	mm	in.	mm			
4.3	108	7.5	190	2.6	65			

Model	Part number	Anvil Speed Working torque		g torque	Max torque Weight		Length		Air cons. average		Air cons. @ load		Sound level	Vibration	Inner hose diameter					
		inch	RPM	ft-lbs.	Nm	ft-lbs.	Nm	lbs	kg	inch	mm	cfm	l/s	cfm	l/s	dBA	m/s² (k)	in	mm	in
CP77320	894 107 7321	1/2	9,410	52 - 285	70 - 387	460	625	2.2	1.0	41/4	108	5.5	2.6	22	10.2	95.5	10.8 (1.42)	3/8	10	1/4

All models: Hose int. %" (10 mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check tool documentation.

### STANDARD OR MAGNETIC 1/2" SOCKET SETS

	Model	Part #	Туре	Pc	Set content
1	SS4114	894 016 4458	Metric	14	10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 26 & 27 mm
J	SS4013	894 016 4465	SAE	13	7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1, 1-1/16, 1-1/8, & 1-1/4"

<b>SS4112G</b> 894 016 4462	Metric	12	10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20 & 21 mm
SS4011G 894 016 4469	SAE	11	<sup>3</sup> / <sub>8</sub> , <sup>7</sup> / <sub>16</sub> , <sup>1</sup> / <sub>2</sub> , <sup>9</sup> / <sub>16</sub> , <sup>5</sup> / <sub>8</sub> , <sup>11</sup> / <sub>16</sub> , <sup>3</sup> / <sub>4</sub> , <sup>13</sup> / <sub>16</sub> , <sup>7</sup> / <sub>8</sub> , <sup>15</sup> / <sub>16</sub> & 1"

### 2 STAGE COMPOSITE 1/4" FRL

Part#	Tuna	Max. Flow Rate					
Fail#	Type	cfm	l/sec				
894 017 1944	NPT	74	34				
894 017 1927	BSP	74	34				

### **TUNE-UP KIT**

Model	Tune-up Kit
CP7732C	894 017 3823

Chicago Pneumatic also offers a large range of air tools, accessories, and workshop equipment to optimize your air tools durability and performance: Check www.cp.com website for more information.



www.cp.com