



Chicago
Pneumatic

CP6763 - Compact, Robust & Powerful 3/4" impact for industrial maintenance applications



Benefits

- ▶ Compact & Versatile for Industrial Maintenance applications
- ▶ Robust for the roughest enviroments and toughest usages
- ▶ Powerful to loose vitually any bolts up to M27 (ISO 10,9)

Features

- ▶ 3/4" impact wrench with Dual retainer
- ▶ Shorts dimensions and narrow side-to-center for easy access
- ▶ Robust Steel Clutch housing
- ▶ Powerfull Twin hammer clutch: 1,200 ft.lbs (1,630 Nm)
- ▶ Combined power regulator with forward/reverse

Technical description		
Part number	6151590400	
Model	CP6763	
Handle type	Pistol	
Square drive	3/4"	
Working Torque Range (fwd)	350-1290 Nm	260-950
Maximum Torque (reverse)	1630 Nm	1200 ft.lbs
Free speed	6300 rpm	
Blows per minute	900	
Net weight	5.5 kg	12.1 lb
Power/weight ratio	296.4 Nm/kg	99.2 ft.lb/lb
Length	222 mm	8.74"
Side to center	41 mm	1.6"
Actual air consumption	14.2 l/s	30 cfm
Air inlet thread size	0.375 "	
Min. hose size	13 mm	1/2"
Noise level	96 db(A)	
Sound Power	107 db(A)	
Vibration α (ISO-28927-2)	9.4 m/s²	
Vibration K (ISO-28927-2)	1.3 m/s²	
Socket retainer	Ring	
Clutch type	Twin Hammer	
Bolt size	M27	
Box dimensions	224*90*232	