

Tailor-made solutions for high demands



Scrubmaster
B30 / CL



Scrubmaster
B45 CLH



Scrubmaster
B45 CL



Scrubmaster
B45 CL WB

Technical Data Scrubmaster	B30	B45	B30 CL	B45 CL*	B45 CL WB
Working width, scrubbing	43 cm	43/51 cm	43 cm	43/51/65 cm	50 cm
Squeegee width	76 cm	76/86 cm	76 cm	76/86/95 cm	86 cm
Theoretical area coverage	1,700 m ²	1,700/2.000 m ²	1,900 m ²	1,900/2,300/2,900 m ²	2,200 m ²
Brush system	1 plate	1 plate	1 plate	1/1/2 plate	2 cylindrical
Brush diameter	43 cm	43/51 cm	43 cm	43/51/33 cm	10 cm
Drive	24 V battery PowerFlow	24 V battery PowerFlow	24 V battery Wheel drive	24 V battery Wheel drive	24 V battery Wheel drive
Battery capacity	80 Ah	80 or 105 Ah	80 Ah	105 Ah/75 Ah DTC	105 Ah
Working speed to	4 km/h	4 km/h	4.5 km/h	4.5 km/h	4.5 km/h
Total output	1.13 kW	1.13 kW	1.31 kW	1.31 kW	1.31 kW
Volumes clean/ dirty water tank	30/30 l	42/42 l	30/30 l	42/42 l	42/42 l
Operating time (max.)	110 min	155 min	100 min	140 min	140 min
Width without/ with squeegee	50/76 cm	50/76/56/86 cm	50/76 cm	50/76/56/86/ 67/86 cm	60/86 cm
Length with squeegee	127 cm	127/135 cm	127 cm	127/135/137 cm	124 cm
Height above handlebar	110 cm	112 cm	110 cm	112 cm	112 cm
Noise at ear of operator	64 dB(A)	64 dB(A)	64/61 dB (A)	64/63/66/63** dB(A)	68/65 dB (A)