

Rexline Indication Layer Rubber Sheeting



Rubber Sheeting Roll REXLINE IL (INDICATION LAYER) comes in 40, 50 and 60 Duro with an Orange indication layer for safety and reliability. REXLINE IL has good UV Light protection and is available with a CN bonding layer to give excellent adhesion to a range of parent metals and surfaces.

This also helps with fast adhesion and effective working rates. Rubber Sheeting Roll REXLINE IL has excellent resistance to dry wear and high impact areas because of its abrasion properties. It is also suitable for wet slurry and fine particle abrasion with high elasticity and flexibility.

REXLINE IL has outstanding physical properties making it the number one choice for wear protection rubber lining applications.

Rexline IL Dimension

Available Dimensions	TOP BLACK LAYER THICKNESS	ORANGE INDICATION LAYER THICKNESS	CN BONDING LAYER THICKNESS
-------------------------	------------------------------	--------------------------------------	-------------------------------

Available Dimensions	TOP BLACK LAYER THICKNESS	ORANGE INDICATION LAYER THICKNESS	CN BONDING LAYER THICKNESS
3 x 1500 x 10000 mm	1 mm	1 mm	1 mm
6 x 1500 x 10000 mm	4 mm	1 mm	1 mm
10 x 1500 x 10000 mm	6 mm	3 mm	1 mm
12 x 1500 x 10000 mm	8 mm	3 mm	1 mm
20 x 1500 x 10000 mm	16 mm	3 mm	1 mm

Technical Specifications

TECHNICAL SPECIFICATIONS	IL 40	IL 50	IL 60
Polymer	NR	NR	NR
Hardness	40± 5 Shore A	50 ± 5 Shore A	60 ± 5 Shore A
Tensile strength (Min)	19 Mpa	19.5 MPa	19.5 MPa
Elongation at break (Min)	656.5%	505%	505%
Specific Gravity	1.08 ± 0.05	1.12 ± 0.05	1.12 ± 0.05
Abrasion Resistance (Max)	126 mm ³	91 mm ³	91 mm ³
Tear resistant Angular (Min)	61 Kg/cm	61 Kg/cm	61 Kg/cm

Search ...

Recent Posts