

### Columbia R LP



Models: 1515 LP - 2015 LP



Models: 1211 LP



Models: 1515 LP/2015 LP

#### Equipped with:


- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling (three phase models).
- Three ceramic coated pistons (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve.
- Low voltage and delayed Total Stop (three phase model).
- Suction and delivery S. S. valves.
- Integrated detergent suction with external suction probe.
- Pressure regulator.
- Glycerine pressure gauge.
- Hose reel (**optional**).
- Accessory holder.
- Power cable holder.
- Steel frame.
- Steel cover.

#### Standard equipment:

- 3.700.0036 Gun M22 - 3/8" (mod 1211 LP).



- 3.700.0030 Gun M22 - 3/8" with rotating coupling (mod. 1515 LP/2015 LP).



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045 (mod. 1211 LP/2015 LP)

- 3.103.0053 Nozzle type 060 (mod. 1515 LP)



- 4.618.0049 High pressure hose 8 m (mod. 1211 LP)

- 4.618.0143 High pressure hose 10 m (mod. 1515 LP/2015 LP).



- Power cable 5 m (mod. 1211 LP)

- Power cable 6 m (mod. 1515 LP - 2015 LP)

#### Optional:

- 6.608.0068 High-pressure hose reel (hose not included)



**VERSION**  
**60 Hz**  
**AVAILABLE**  
**DETAILS PAGE 9**

	COLUMBIA R 1211 LP	COLUMBIA R 1515 LP	COLUMBIA R 2015 LP
code	8.654.0071	8.654.0073	8.654.0072
operat. pressure/max	120/150 bar-1740/2175 psi	150 bar-2175 psi	200 bar-2900 psi
delivery rate	660 l/h-2.91 GPM	900 l/h-3.96 GPM	900 l/h-3.96 GPM
abs. power/voltage	3000W - 230V~50Hz 1 ph	5000W - 400V~50Hz 3 ph	7000W - 400V~50Hz 3 ph
motorpump type/RPM	MP3/1450 RPM	MPW3/1450 RPM	MPW3/1450 RPM
max. water inlet temperature	40 °C	40 °C	40 °C
dimension/weight	50x90x83cm / 37 kg - 81 lbs	50x90x83cm / 49 Kg - 108 lbs	50x90x83cm / 51 Kg - 112 lbs