

Thermic 17 HW Hot water self-contained unit with integrated electric generator



Equipped with:

- Three ceramic pistons, brass linear pump head with built-in by-pass valve. • By-pass thermal protection with safety valve. • 2 cylinder water cooled diesel engine with electrical start.
- Integrated electric generator. • Auxiliary belt driven sturdy alternator. • Lombardini diesel engine 15LD400 (air cooled). • Belt driven pump (1.450 RPM). • Automatic engine RPM regulator. • Socket tool max 1.5 kW • Front panel with engine function led and automatic power cut-off. • Unique diesel tank for engine and burner. • Battery included.

Standard equipment:

- 3.700.0043 Gun MV 975 3/8" M with quick connection



- 6.602.0043 Lance 900 mm with quick connection.



- 3.103.0056 Nozzle type 075



- 4.618.0143 High pressure hose 10 m



Optional:

- 6.608.0013 Varnished soundproofing steel cover set



Thermic 17 HW	
code	8.601.0052
operat. pressure	200 bar-2900 psi
delivery rate	1320 l/h-5.82 GPM
engine type/hp	Lombardini 15LD400/17
pump type/RPM	CL5/1600 RPM
max. water inlet/outlet temp.	40/140 °C
dimension/weight	113x75x85cm / 220 Kg - 480 lbs