



Speed


Standard equipment:




- 5.511.1688
PP brush Ø 430 mm - 17"



- 4.508.X468
Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm
- 4.508.X467
Rear squeegee blade L.870 mm Shore 40 Th. 3 mm



- 0.108.0042
On-board Battery charger CBHD1 24V 10A
only for model code:
8.524.1002
8.524.0002



- 2 x 0.107.0061
Maintenance free battery 12 MFP 50 - 12V 50Ah
only for model code:
8.524.0002



- Suitable to work in high congested areas like wellness centres and medical environments in general, gyms, retail outlets, car shops, sales points and health care
- Solution water filter and solenoid valve (battery model only)
- User friendly control panel
- Hour meter (optional)
- Recovery water tank with visual inspection
- Reclining handle with control lever (battery model only)
- Low noise operation thanks to the protected positioning of vacuum motor
- Recovery tank drain hose with adjustable flow system
- Indicator of the solution water tank fill level
- Easy access to the recovery tank
- Non-marking wheels.



Watch the video on youtube:
www.youtube.com/lavorpro

	Speed 45E	Speed 45B	Speed 45B
code	8.524.3302	8.524.1002	8.524.0002
power supply	230 V - 50 Hz	24V (battery charger included)	24V (batteries and charger included)
scrubbing / squeegee width	450 / 800 mm	450 / 800 mm	450 / 800 mm
max working capacity	1575 m ² /h	1575 m ² /h	1575 m ² /h
solution tank capacity	25 l / 6.61 gal	25 l / 6.61 gal	25 l / 6.61 gal
recovery tank capacity	25-28 l / 6.61 gal	25-28 l / 6.61 gal	25-28 l / 6.61 gal
traction	mechanical	mechanical	mechanical
RPM / pressure on the brushes	140/25 kg / 39,68 lbs	150/18 kg / 39,68 lbs	150/18 kg / 39,68 lbs
brush motor power	550 W	450 W	450 W
detergent solution system	mechanical	solenoid valve	solenoid valve
depression / vacuum motor	1100 mmH ₂ O/400 W	1100 mmH ₂ O/370 W	1100 mmH ₂ O/370 W
dimensions / weight	106x50x88 cm / 65 kg	106x50x88 cm / 87kg	106x50x88 cm / 87kg



User friendly analogic control panel. Control lever for brush operation and detergent water outflow. ON/OFF and battery cutout key switch, brush and vacuum motor switch, detergent dosing knob (optional), Thermal circuit breaker to protect vacuum and brush motor, battery level indicator, hour meter (optional).

Optional accessories:



- 0.107.0050 Battery AGM 12V 55Ah



- 4.508.1178 Polyurethane front blade L.830 TH. 3
- 4.508.1177 Polyurethane rear blade L.870 TH. 4

Indicator of clean water tank level. Detergent solution regulation. Recovery tank drain hose with adjustable flow system.



- 5.511.1713 Tynex brush Ø 430 mm-17"
- 5.511.1711 PP 0,03 brush Ø 430 mm-17"
- 5.511.1712 PES brush Ø 430 mm - 17"



- 5.511.1095 EWU pad driver Ø 430 mm-17"



- 6.508.0032 Abrasive pad Ø 430 mm-17" - beige (5 pcs.)
- 6.508.0039 Abrasive pad Ø 430 mm-17" - green (5 pcs.)
- 6.508.0046 Abrasive pad Ø 430 mm-17" - black (5 pcs.)



Easy access to recovery water tank with visual inspection. Extremely silent (62 dB) thanks to the particular housing of the vacuum motor and the use of soundproofing material.



- 4.512.0068 Extension electric cord 15 m with Schuko plug

Thanks to the special squeegee support it is easily possible the tilting of the machine to carry out the drying of the floor without scrubbing. The oversize wheels facilitate maneuverability and effortless use.

