Additel 914A Handheld Pneumatic Pressure Test Pump

- Generate 95% vacuum to 375 psi (25 bar) pressure
- Portable, only 3.3 lb
- Great stability and high resolution
- Minimal maintenance
- Hand-tight quick connectors



ddite

Metrology Made Simple

OVERVIEW

The 914A Pneumatic Pressure Test Pump is a hand operated pressure pump designed to generate pressure from 95% vacuum to 375 psi (25 bar). A high-quality screw press is designed for fine pressure adjustment, with an adjustment resolution up to10 Pa (0.1 mbar). A specially designed shut-off valve makes the pressure as stable as possible during calibration. A built-in gas-liquid isolator protects the pump from moisture and dirt to reduce the need for maintenance. Two hand-tight quick connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The 914A is an ideal comparison test pump for pressure instruments calibration.

FEATURES

Portable:


- Only 3.3 lb (1.5 kg)
- Adjustment Resolution
 10 Pa (0.1 mbar)
 High-quality screw press for fine pressure adjustment
- Great Stability
 A specially designed shut-off valve makes the pressure as stable as possible during calibration
- Durable and Minimal Maintenance Built-in gas-liquid isolator protects the pump from moisture and dirt
- Easy-to-use
- Hand-tight Quick Connectors

Allows easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches

ORDERING INFORMATION

Model Number

Manual: 1 pc



Carrying case (914A-X-SET models only)

Optional Accessories

Model number	Description
ADT102	Adapters and fittings, 1/4NPT male to various male and female connection (25 pcs). More information shown on page 70.
ADT103	Adapters and fittings, 1/4NPT (1/2NPT, 1/4BSP, 1/2BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs). More information shown on page 71.
ADT100-HTK-8K	Hose test kit, 5 feet flexible hose, 8,000 psi, user selectable male (1/4NPT, 1/2NPT, 1/4BSP, 1/2BSP, M20) to user selectable female hand tight quick connector.
9901-914	Carrying Case for one 914A pump and two 681 gauges or 672 calibrators
ADT914A-MK	Maintenance kit for Additel 914A pump

Note: For oil free applications contact Additel.

Body: SS, aluminum Seals: Buna-N, PTFE, Copper Alloy

Adjustment Resolution: 10 Pa (0.1 mbar).

- Piston volume: 21 ml (1.3 in³)
- Connection Hand-tight connectors for both test gauge and reference gauge. 1/4NPT female, 1/2NPT female, 1/4BSP female, 1/2BSP female, or M20X1.5 female

Generated Pressure Range: 95% vacuum to 375 psi (25

- Dimensions Height: 5.12" (130 mm) Base: 9.45" (240 mm) x 4.72" (120 mm)
- Weight: 3.3 lb (1.5 kg).
- Warranty: 1 year

SPECIFICATIONS

bar) positive pressure

Material: Ram/adapters: SS

Media: Air.