Specifications for imageCLASS MF246dn

PRINT Drinting Mathed			
-	Monochrome Laser Beam Printing		
	27ppm		
	600 x 600dpi		
Print Quality with Image Refinement Technology	1,200 x 1,200dpi (equivalent)		
Warm-Up Time (From Power On)	13.5secs. or less		
First Print Out Time (FPOT) A4	Approx. 6.0secs.		
Recovery Time (From Sleep Mode)	2.0secs. or less		
Print Language	UFR II LT, PCL 6		
Auto Duplex Printing	Standard		
Available Paper Size for Auto Duplex Print	A4, Letter, Legal ^(*1) , Indian Legal, Foolscap		
Print Margin	5mm-top, bottom, left and right (Other sizes than Envelope)		
	10mm-top, bottom, left and right (Envelope)		
СОРУ		·	
Copy Speed (A4)	27ppm		
Copy Resolution	600 x 600dpi		
First Copy Time (FCOT) A4	Approx. 9.0secs.		
Maximum Number of Copies	Up to 999 copies		
Reduce / Enlargement	25 - 400% in 1% increments		
	Memory Sort, 2 on 1, 4 on 1, ID Card Copy		
SCAN			
Scan Type	Colour Contact Image Sensor		
Scan Resolution	Optical	Up to 600 x 600dpi	
	Driver Enhanced	Up to 9,600 x 9,600dpi	
Maximum Scan Size	Platen Glass	Up to 216 x 297mm	
Scan Speed (*2)	Platen Glass	Approx. 3.0secs. per sheet (mono)	
		Approx. 4.0secs. per sheet (colour)	
	ADF (A4)	20 / 15ipm (mono / colour)	
Colour Depth	24-bit		
·	Yes, USB and Network		
Push Scan (Scan To PC) with MF Scan Utility	,		
Scan To Cloud	Yes, MF Scan Utility		
Scan Driver Compatibility	TWAIN, WIA, ICA		
SEND			
SEND Method	SMB, SMTP (E-mail), POP (E-mail)		
Colour Mode	Full Colour, Grayscale, Monochrome		
	300 x 300dpi		
	JPEG, TIFF, PDF		
FAX			
	Up to 33.6 Kbps		
	Up to 200 x 400dpi		
	MH, MR, MMR		
	Up to 256 pages		
One-touch Dial	4 dials		
	Up to 100 dials		
	Max. 103 dials / Max. 50 destinations		
Sequential Broadcast	Max. 114 destinations		
' ' '	No		
Receive Mode	Fax Only, Manual, Answering Machi	ne, Fax / Tel Auto Switch	

Memory Backup	Permanent Fax Memory Back-up		
Fax Features	Fax Forwarding, Dual Access, Remote Reception, PC Fax (Transmission only), DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports		
PAPER HANDLING			
Auto Document Feeder (ADF)	35 sheets (80g/m²)		
Available Paper Size for ADF	A4, B5, A5, B6, Letter, Legal		
	(Min. 105 x 148mm to Max. 216 x 356mm)		
Paper Input	Standard Cassette	250 sheets	
	Multi-Purpose Tray	1 sheet	
Paper Output (Based on 68g/m²)	100 sheets (face down)		
Paper Size	Standard Cassette	A4, B5, A5, Legal, Letter, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal Custom (Min. 76.2 x 210mm to Max. 216 x 356mm)	
	Multi-Purpose Tray	A4, B5, A5, Legal, Letter, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal	
		Custom (Min. 76.2 x 127mm to Max. 216 x 356mm)	
Paper Weight	Standard Cassette	60 to 163g/m ²	
	Multi-Purpose Tray	60 to 163g/m ²	
Paper Type	Plain, Heavy, Recycled, Color, Label, Index Card, Envelope		
CONNECTIVITY & SOFTWARE		·	
Standard Interface	Wired	High-Speed USB 2.0	
Network Interface	Print	10 / 100 Base-T Ethernet LPD, RAW, IPP / IPPS, WSD-Print (IPv4, IPv6)	
Network interface	Scan	WSD-Scan (IPv4, IPv6)	
	TCP / IP Application Services:	Bonjour(mDNS), DHCP, BOOTP, RARP, Auto IP (IPv4), DHCPv6 (IPv6)	
	Management	SNMPv1/v3 (IPv4, IPv6), HTTP / HTTPS, SNTP	
Network security	Wired	IP / Mac address filtering, SNMPv3, SSL (HTTPS / IPPS), IEEE802.1x	
Mobile Printing Capability	Canon PRINT Business, Canon Print Service, Google Cloud Print™, Apple AirPrint™, Mopria® Print Service		
Compatible Operating Systems	Microsoft® Windows® 10 (32 / 64-bit), Windows® 8.1 (32 / 64-bit), Windows® 8 (32 / 64-bit), Windows Vista® (32 / 64-bit), Windows Vista® (32 / 64-bit), Windows® Server 2012 R2 (64-bit), Windows® Server 2008 R2 (64-bit), Windows® Server 2008 (32 / 64-bit), Windows® Server 2003 R2 (32 / 64-bit), Windows® Server 2003 (32 / 64-bit), Windows® Server 2003 (32 / 64-bit), Mac OS X (*4) 10.6.8~, Linux (*4)		
Software Included	Printer driver, Fax driver, Scanner driver, MF Scan Utility, AddressBook Tool, Toner Status, Send Setting Tool		
GENERAL			
Device Memory	512MB		
Operational Panel	6-line Monochrome LCD Touch Sc	reen	
Dimensions (W x D x H)	390 x 371 x 360mm (Cassette clos	•	
Weight	390 x 441 x 360mm (Cassette opened) Approx. 12.1kg (without cartridge)		
	Approx. 12.7kg (with cartridge)		
Power Consumption	Maximum	1,150W or less	
	During Operation (Avg.)	Approx. 490W	
	During Standby (Avg.)	Approx. 5.7W	
	During Sleep (Avg.)	Approx. 1.3W (USB connection) Approx. 1.4W (Wired LAN connection)	

Noise level (*5)	During Operation	Sound Pressure Level: 52.0dB	
		Sound Power Level: 6.6B	
	During Standby	Sound Pressure Level: Inaudible (*6)	
		Sound Power Level: 43dB	
Operating Environment	Temperature: 10 - 30°C		
	Humidity: 20 - 80% RH (no condensation)		
Power Requirement	AC 220 - 240V (±10%), 50 / 60Hz (±2Hz)		
Consumables (*7)	Toner (Standard)	Cartridge 337: 2,400 pages	
		(bundled: 1,700 pages)	
Monthly Duty Cycle (*8)	15,000 pages		

Specifications are subject to change without notice.

*1	Legal refers to paper measuring 215.9 x 355.6mm (8.5 x 14 inches).
*2	Scanning with 300 x 300 dpi resolution. The communication time is not included.
*3	Based on ITU-T #1 Chart (standard mode)
*4	Drivers for Mac OS can be downloaded from the here website when available.
*5	Measured in accordance with ISO 7779, declared noise emission in accordance with ISO 9296.
*6	"Inaudible" indicates the sound pressure level of each bystander position is below the ISO 7779 absolute criteria for the background noise level.
*7	Declared yield in accordance with ISO / IEC 19752.
*8	Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon laser devices, and does not refer to actual maximum image output per month