



Oil & Fuel Hose

OIL DELIVERY HOSE

APPLICATION/USE

Application : The hose is for the discharge of gasoline, oil and other petroleum based products on tank and docks
 Tube : Black Nitrile RMA class A compound (high oil resistance)
 Reinforcement : Spiral-plyed synthetic fabric with static wire
 Cover : Abrasion, oil, weather & ozone resistant compound

Temperature : -20°F to 180°F (-30°C to 80°C)
 Safety Factor : 4 : 1
 Branding : MONDEA Oil Delivery Hose



PART No.	ID		OD		MAX. WORK PRESSURE		STANDART LENGTH		BENDING RADIUS		APPROX WEIGHT	
	in	mm	in	mm	psi	bar	(M)	(FT)	in	mm	(lbs/ft)	(Kg/m)
025ODH10	1.00	25	1.38	35	150	10	60	200	10	250	0.43	0.63
032ODH10	1.25	32	1.65	42	150	10	60	200	13	320	0.53	0.78
038ODH10	1.50	38	1.89	48	150	10	60	200	15	380	0.61	0.91
045ODH10	1.77	45	2.17	55	150	10	60	200	18	450	0.71	1.06
051ODH10	2.00	51	2.45	62	150	10	60	200	20	500	0.89	1.33
063ODH10	2.50	63	3.92	74	150	10	60	200	26	650	1.08	1.61
076ODH10	3.00	76	3.51	89	150	10	60	200	28	700	1.38	2.06
089ODH10	3.50	89	4.02	102	150	10	60	200	35	900	1.62	2.41
102ODH10	4.00	102	5.65	118	150	10	60	200	39	1000	2.29	3.42
114ODH10	4.50	114	5.07	129	150	10	60	200	47	1200	2.43	3.62
127ODH10	5.00	127	5.63	143	150	10	60	200	51	1300	2.92	4.35
152ODH10	6.00	152	6.61	168	150	10	30	100	59	1500	3.58	5.33
203ODH10	8.00	204	8.79	223	150	10	30	100	79	2000	6.33	9.44
025ODH20	1.00	25	1.43	36	300	20	60	200	10	250	0.41	0.62
032ODH20	1.25	32	1.70	43	300	20	60	200	13	320	0.51	0.76
038ODH20	1.50	38	1.94	49	300	20	60	200	15	380	0.59	0.88
045ODH20	1.77	45	2.25	57	300	20	60	200	18	450	0.72	1.08
051ODH20	2.00	51	2.51	64	300	20	60	200	20	500	0.84	1.25
063ODH20	2.50	63	2.96	75	300	20	60	200	26	650	0.99	1.48
076ODH20	3.00	76	3.50	89	300	20	60	200	28	700	1.25	2.86
089ODH20	3.50	89	4.09	104	300	20	60	200	35	900	1.87	2.79
102ODH20	4.00	102	4.71	120	300	20	60	200	39	1000	2.64	3.93
114ODH20	4.50	114	5.18	132	300	20	60	200	47	1200	2.97	4.43
127ODH20	5.00	127	5.80	147	300	20	60	200	51	1300	3.81	5.67
152ODH20	6.00	152	6.80	173	300	20	30	100	59	1500	5.05	7.52
203ODH20	8.00	204	9.23	234	300	20	30	100	79	2000	11.25	16.77

Max diameter available : up to 30"

* Please contact us if you should require sizes / lengths or specifications other than the ones indicated above