


# Technical Specification


ITEM		UNITS	SPECIFICATION					REMARKS
MODEL			FRc-1000	FRc-2000	FRc-3000	FRc-5000	FRc-7501C1	
CAPACITY		VA	1000	2000	3000	5000	7500	MAXIMUM
AC INPUT	VOLTAGE	V	170 – 250					
	FREQUENCY	Hz	50					
	PROTECTION		MCB					
AC OUTPUT	VOLTAGE	V	220 ± 2%					
	FREQUENCY	Hz	50					
RESPONSE TIME		s	0,1					
OPERATION TEMPERATURE		°C	0-40					
DIMENSION		mm	320x242x210		480x230x467		630x264x682	D x W x H
WEIGHT		Kg	12.5	18	43	47.5	62.5	GROSS

ITEM		UNITS	SPECIFICATION			REMARKS
MODEL			FRc-7501C3	FRc-1002C3	FRc-1502C3	
CAPACITY		VA	7500	10000	15000	
AC INPUT	VOLTAGE	V	THREE-PHASE, 4 WIRE 380			+10%, -20%
	FREQUENCY	Hz	50			
	PROTECTION		MCB			
AC OUTPUT	VOLTAGE	V	380 ± 5%			
	FREQUENCY	Hz	50			
RESPONSE TIME		s	0,1			
OPERATION TEMPERATURE		°C	0-40			
DIMENSION		mm	630x264x682	490x530x1140		D x W x H
WEIGHT		Kg	75	135	160	GROSS


SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.




REAR PANEL  
FRc 1000 & FRc 2000



REAR PANEL  
FRc 3000 & FRc 5000



REAR PANEL  
FRc 7501C1 & FRc 7501C3



REAR PANEL  
FRc 1002C3 & FRc 1502C3

CONTACT PERSON :



481-4270010-110