

BW WAYLUBE BSH- series

ISO-L-HG type of slideway oil

Descriptio BSH-series oils are mineral oil based slideway oil

Benefits

1. Anti stick-slip performance due to high performance takifier.
2. Low pour point, good water separability and foam characteristic.
3. Good oxidation stability.

test items	BSH-32	BSH-46	BSH-68	BSH-150	BSH-220	test method
appearance, conc	light yellow	light yellow	light yellow	yellow	yellow	VISUAL
specific gravity, 15/4°C	0.86	0.86	0.86	0.875	0.88	ASTM D1298
kin. viscosity, 40°C, cSt	32	46	68	150	220	ASTM D445
viscosity index	105	105	105	100	100	ASTM D2270
flash point, COC, °C, Min.	220	220	220	240	240	ASTM D92
pour point, °C, Max.	-27.5	-27.5	-27.5	-20	-20	ASTM D97
foaming, sq.l~III, ml	10/0	10/0	10/0	10/0	10/0	ASTM D892
copper corosion	1B	1B	1B	1B	1B	ASTM D130

*The test results are typical properties of fresh oil, can be changed by quality improvement.

Applicatio Where ISO-L-HG type of slideway oil is needed.
Where a slideway oil containing Takifier is recommended.

Term of validity 12 months from the date of manufacture at sealed state, 0 to 40°C.

Safety informatio Refer to the our MSDS for safety information

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.