



Bobcat®

ATTACHMENT VIBRATORY ROLLER

Compatible models:

Skid Steer Loaders



Compact Track Loaders



One Tough Animal.

VIBRATORY ROLLER



| | REQUIREMENTS | FEATURES & BENEFITS |
|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |  Vibratory Roller: No special requirement. | <ul style="list-style-type: none"> • Free drum oscillation keeps more of the drum in contact with the surface on uneven terrain. • Offset drum design allows the right side of the roller to extend past the machine. This is very useful when compacting next to sidewalks, walls, or curbs. • Durable one-piece drum for extra strength. • Dual-direction vibration motor permits compaction travelling in either direction. • Rubber isolation mounts on the roller reduce vibration transfer to the loader and operator. • Both smooth and padded drums are available. |

Description: The ideal compacting tool for flatwork, trenches and asphalt patching jobs. Compacts while moving forward or in reverse. Offset drum design lets you get right next to sidewalks, walls or curbs. Drum oscillation keeps the roller in contact with the surface on uneven terrain.

| TECHNICAL SPECIFICATIONS | | | | | | | | | | | |
|---------------------------------------|-------------|--------------------|---------------------|----------------|-------------------|------------------------------|---------------------------|-------------|----------------------|--------------|-----------------------------|
| Description | Part Number | Working Width (mm) | Wheel Diameter (mm) | Number of Pads | Oscillation ± (°) | Dynamic Force (kN) @ (l/min) | Frequency (vpm) @ (l/min) | Weight (kg) | Control Kit Required | Working Flow | First Use Installation Time |
| Vibratory Roller, 122 cm, Padded Drum | 7165403 | 1219 | 643 | 72 | 12 | 63.4 @ 75 | 2879 @ 75 | 807 | No | Standard | None |
| Vibratory Roller, 185 cm, Padded Drum | 7165401 | 1854 | 643 | 102 | 7.5 | 63.5 @ 90 | 2882 @ 90 | 993 | No | Standard | None |
| Vibratory Roller, 122 cm, Smooth Drum | 7165404 | 1219 | 660 | 0 | 12 | 63.4 @ 75 | 2879 @ 75 | 811 | No | Standard | None |
| Vibratory Roller, 185 cm, Smooth Drum | 7165402 | 1854 | 660 | 0 | 7.5 | 63.5 @ 90 | 2882 @ 90 | 1002 | No | Standard | None |
| Vibratory Roller, 203 cm, Smooth Drum | 7165400 | 2032 | 660 | 0 | 7.5 | 63.5 @ 90 | 2882 @ 90 | 1052 | No | Standard | None |

| COMPATIBILITY CHARTS | | | | | | | | | | | | | | | | | | | | | | | |
|---------------------------------------|-------------|-----------------------|------|--------|-------|--------|-------|--------|--------|--------------------|------|------|--------|--------|--------|--------|--------|-------|--------|--------|-------|--------|--------|
| Description | Part Number | Compact Track Loaders | | | | | | | | Skid-Steer Loaders | | | | | | | | | | | | | |
| | | MT55 | T450 | T590/H | T66/H | T650/H | T76/H | T770/H | T870/H | S70 | S100 | S450 | S510/H | S530/H | S550/H | S570/H | S590/H | S66/H | S630/H | S650/H | S76/H | S770/H | S850/H |
| Vibratory Roller, 122 cm, Padded Drum | 7165403 | | X | X | X | | | | | | | X | X | X | X | X | X | | | | | | |
| Vibratory Roller, 185 cm, Padded Drum | 7165401 | | | X | X | X | X | X | | | | | | | X | X | X | X | X | X | X | X | X |
| Vibratory Roller, 122 cm, Smooth Drum | 7165404 | | X | X | X | | | | | | | X | X | X | X | X | X | | | | | | |
| Vibratory Roller, 185 cm, Smooth Drum | 7165402 | | | X | X | X | X | X | | | | | | | X | X | X | X | X | X | X | X | X |
| Vibratory Roller, 203 cm, Smooth Drum | 7165400 | | | | | X | X | X | X | | | | | | | | | X | X | X | X | X | X |

ALWAYS START WITH THE VIBRATORY ROLLER ON THE GROUND. ROTATION IN THE SAME DIRECTION AS THE MACHINE!

SCAN HERE



multico

Asia's Equipment Specialist

Multico Equipment Indonesia, PT.
Plaza Kelapa Gading Blok C No. 12 Jl.Raya Boulevard Barat,
Kelapa Gading, Jakarta Utara, 14240
Phone: +62 21 4585 1122 / Fax : +62 21 2245 5028
www.multicoequipmentid.com



Bobcat[®]

WWW.BOBCAT.COM

DOOSAN

Bobcat is a Doosan Company.

Doosan is a global leader in construction equipment, power & water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2022 Bobcat Company. All Rights Reserved.

Certain specifications are based on engineering calculations and are not actual measurements. Specifications are provided for comparison purposes only and are subject to change without notice. Specifications for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of Bobcat units may show other than standard equipment.