


DH4500 Series

Polysulfone Rotameter


Polysulfone(PSU) or PC body,Fittings made of PVC ABS or SS Floats Capable of withstanding higher temperatures, Thread joint and panel-mounted fittings are easy to install,economical and durable

Technical Parameters of DH4500 Flow Meter


Model	DN	Range		Accuracy	° C Temperature	Mpa Pressure
		GPM	LPM			
DH45-15E	15	0.1-1	0.5-4	±4%	0-60 0-100	≤0.6
DH45-15G		0.2-2	1-7			
		0.5-5	1.8-18			
DH45-15EC	15	0.1-1	0.5-4			
DH45-15GC		0.2-2	1-7			
		0.5-5	1.8-18			
DH45-25E	25	0.8-8	3-30			
DH45-25G		1-10	4-40			
DH45-32E	32	1.2-12	5-50			
DH45-32G		2-20	8-80			
		2.5-25	10-100			
DH45-50E	50	2.5-25	10-100			
DH45-50G		5-45	20-180			
		7-70	25-250			
DH45-65E	65	25-110	80-400			
DH45-65G		40-160	150-650			
		50-250	200-1000			




Joint



Male



Female



Elbow

DH4500 Dimensions for installation

Model	L	D	Joint			Male		Female		Elbow				
			L1	B1	B2	L2	C	L3	E	L4	F	G	A	H
DH45-15E DH45-15G	100	Φ42	150	Φ20	Φ26	170	1/2" BSP 1/2" NPT	/	/	155	52	27	Φ13	1/2" BSP 1/2" NPT
DH45-15E DH45-15G	160	Φ50	210	Φ20	Φ26	225	1/2" BSP 1/2" NPT	210	1/2" BSP 1/2" NPT	220	56	27	Φ13	1/2" BSP 1/2" NPT
DH45-25E DH45-25G	170	Φ59	230	Φ32	Φ39	250	3/4" NPT	225	3/4" BSP 3/4" NPT	270	70.5	28	Φ20	3/4" BSP 3/4" NPT
DH45-32E DH45-32G	225	Φ72	290	Φ40	Φ49	310	1" NPT	290	1" BSP 1" NPT	345	86	35	Φ26	1" BSP 1" NPT
DH45-50E DH45-50G	290	Φ98	375	Φ63	Φ73	400	2" NPT	370	2" NPT	440	109	40	Φ45	2" BSP 2" NPT
DH45-60E DH45-65G	325	Φ120	420	Φ75	Φ89	445	2 1/2" NPT	420	2 1/2" NPT	/	/	/	/	/