



Main

Range of product	EOCR
Device short name	EOCR-3MZ2
Product or component type	Protection relay
Protection type	Overload, $I_n > OC$ setting Underload, $I_n < UC$ setting Locked rotor for starting, $I_n > 2...8$ times OC setting Locked rotor for running, $I_n > 1.5...5$ times OC setting Sensitivity to phase loss Phase unbalance, 10..50 % Earth fault, $I_g > I_g$ setting Sensitivity to phase reverse
Product specific application	Motor protection
Network type	AC
Network frequency	50..60 Hz
Protection adjustment range	0.5...60 A
Tripping threshold	0.5...32 A (inverse and thermal) 0.5...60 A (definite) 0.03...10 A (definite) - earth fault current

Complementary

[Us] rated supply voltage	24 V AC/DC
Mounting support	Panel 35 mm DIN rail
Contacts type and composition	1 NC + 1 NO (OL/GR)
Short-circuit and overload protection	By 4 A gG fuse
[Ue] rated operational voltage	Power circuit : 600 V AC 50..60 Hz UL Power circuit : 690 V AC 50..60 Hz CSA Power circuit : 690 V AC 50..60 Hz IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-4-1
Reset	Electrical 0...1 s by interruption of power supply Manual reset Automatic reset 0.5...1200 s
Time delay type	D-Time : 0...200 s O-Time : 0.2...30 s (definite) O-Time : 1...30 class (inverse and thermal) U-Time : 0.5...30 s E-Time : 0.05...10 s


Ed-Time : 0...30 s

Display type	7 segments LED Bar graph
Power consumption per relay	< 3 W
Connections - terminals	Control circuit : 2 cable 1...1.5 mm ² - flexible - with cable end - M3 Control circuit : 2 cable 1...1.5 mm ² - flexible - without cable end - M3 Control circuit : 1 cable 1...2.5 mm ² - flexible - with cable end - M3 Control circuit : 1 cable 1...2.5 mm ² - flexible - without cable end - M3
Tightening torque	0.8...1.2 N.m for control circuit - cable - 4.7 mm head
Height	56.3 mm
Width	70 mm
Depth	108.1 mm
Product weight	0.355 kg

Environment

Standards	IEC 60947-4-1
Product certifications	UL
IP degree of protection	IP20 IEC 60529
Ambient air temperature for operation	-20...60 °C IEC 60947-4-1
Ambient air temperature for storage	-40...85 °C
Operating altitude	2000 m
Fire resistance	650 °C IEC 60695-2-12 960 °C UL 94
Shock resistance	15 gn for 11 ms IEC 60068-2-7
Vibration resistance	4 gn on panel mounting IEC 60068-2-6 2 gn on 35 mm DIN rail IEC 60068-2-6
Dielectric strength	2 kV at 50...60 Hz in between case and circuit IEC 60255-5 1 kV at 50...60 Hz in between contact IEC 60255-5 2 kV at 50...60 Hz in between circuit IEC 60255-5
Surge withstand	6 kV IEC 61000-4-5
Electromagnetic compatibility	Resistance to electrostatic discharge 8 kV air, 6 kV contact IEC 61000-4-2 Resistance to radiated electromagnetic fields 10 V/m level 3 IEC 61000-4-3 Resistance to fast transient 2 kV IEC 61000-4-4 Conducted RF disturbances 10 V EN 61000-4-6 Conducted RF disturbances class A EN 55011
[Ith] conventional free air thermal current	3 A, control circuit
Permissible current	250 V, 3 A AC

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------