

ymbio

High Molecular Weight PVC Label Stock

Code: PL6EMZ

Application:

This PVC label stock has a very good adhesion on curve surface profile of plastic or metal. For example, motorbike decorative cover.

Construction:

#60 matte-white PVC

Solvent based acrylic adhesive

160g/m² Yellow kraft release paper (Lay flat liner)

Description:

- This product group is excellent in properties, such as printability, weatherability and good adhesion.
- > Special designed low tack adhesive makes it easier for a large sticker to apply onto the curved flat substrate surface. Rework is again easier with our design.
- ➤ High adhesion and high holding power makes the sticker firmly stick to the substrate surface.
- The specially design high molecular weight PVC film offers superior properties of water-resistance, heat-resistance, humidity-resistance, and chemical-resistance.
- This product is complied to RoHS requirement.

Specification:

1. Thickness of adhesive $30\pm2(\mu m)$

2. 180° peel adhesion (ASTM-D1000) 1.3~1.6(kg/25mm)

3. Ball tack (PSTC-6 #7) 5~15(cm)

4. Unwinding force (ASTM-D1000) $5\sim15(g/25mm)$

5. Storage condition 23°C, 65%R.H.

Storage validity 1 year

6. Storage validity www.symbioinc.com.tw

Symbio, Inc.

四維精密材料股份有限公司

- 臺北公司/臺北縣三重市光復路一段83巷1號 TEL: (02)29991121
- 桃園公司/桃園市興華路12號 TEL: (03)3612123

Important Notice to Purchaser

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and users assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.



Important Remarks:

- 1. If applying to surfaces treated with machining oil, degrease the surface carefully. Any remains will be a cause for surface contamination or adhesive residue.
- When using this product should be applied evenly across the surface of the pressure to achieve the desired adhesive effect.
- Avoid sunlight and store at room temperature and moderate humidity.
- Rolls of packaging products to be erected straight up, cutting type of product should be in flat. When the products placed on the pallet, each plate height should not exceed one meter, and take up to 10 cm from the ground above.
- The above datasheet is a sample observation value under certain testing conditions, not guaranteed performance.

www.symbioinc.com.tw

Symbio, Inc.

維精密材料股份有限公司

- 臺北公司/臺北縣三重市光復路一段83巷1號 TEL: (02)29991121 桃園公司/桃園市興華路12號 TEL: (03)3612123

Important Notice to Purchaser

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and users assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.