

DIGITAL AC CLAMP METER

MS2000/MS2000G



MS2000

JAW SIZE
Φ55mm/2.2"

CURRENT
AC 2000A



Features:

1. Jaw Size: Φ55mm/2.2"
2. AC Current Measurement up to 2000A
3. Tests AC/DC Voltage, AC Current and Resistance
4. Frequency Measurement (MS2000G)
5. Type -k Thermocouple contact
6. temperature measurement (MS2000G)
7. Diode Check and Continuity test
8. Data Hold and Display Back Light

MS2000G

JAW SIZE
Φ55mm/2.2"

CURRENT
AC 2000A



Specifications		MS2000G
Specifications	Range	Accuracy
DC Voltage	2V/20V/200V	±(0.5%+1)
	1000V	±(1.0%+2)
AC Voltage	750V	
	200V/750V	±(1.0%+5)
AC Current	200A/2000A	±(2.0%+5)
Resistance	200Ω/20KΩ/2MΩ	±(1.2%+2)
Frequency	0~2KHz	±(1.5%+5)
Temperature	-20°C~750°C	±(2%+2)
	-4°F~1832°F	±(2%+4)
Features		
Display	Counts	2000
Jaw Opening		Φ55mm/2.2"
Diode	2.7V	•
Continuity Buzzer	<500	•
Data Hold		•
Display Backlight		•
General		
Power Supply	1x9V/6F22Battery	
Product Size	282mmx104mmx47mm/11"x4.1"x1.85"	
Product Weight	503g/1.1lb	
Safety Rating	CAT.II 1000V	