

快速規範 QUICK SELECTION CHART

提把型式 Handle type	型號 Model Number	能力 Cylinder Capacity	揚程 Stroke	受壓面積 Cylinder Effective Area	總油量 Oil Capacity	本身高 Collapsed Height	主軸內牙 Plunger internal Thread	重量 Weight	
(O) (S)		ton (kN)	(mm)	(cm ²)	(cm ³)	A (mm)	O (in)	(kg)	
	RSC-50	5 (45)	16	6.5	10	41	—*	1.0	
	RSC-51		25	6.5	16	110	3/4"-16	1.0	
	RSC-53		76	6.5	50	165	3/4"-16	1.5	
	RSC-55		127	6.5	83	215	3/4"-16	1.9	
	RSC-57		177	6.5	115	273	3/4"-16	2.4	
	RSC-59		232	6.5	151	323	3/4"-16	2.8	
	RSC-101	10 (101)	26	14.5	38	89	#10-24UN	1.8	
	RSC-102		54	14.5	78	121	1"-8	2.3	
	RSC-104		105	14.5	152	171	1"-8	3.3	
	RSC-106		156	14.5	226	247	1"-8	4.4	
	RSC-108		203	14.5	294	298	1"-8	5.4	
	RSC-1010		257	14.5	373	349	1"-8	6.4	
	RSC-1012		304	14.5	441	400	1"-8	6.8	
	RSC-1014		356	14.5	516	450	1"-8	8.2	
	RSC-151		15 (142)	25	20.3	51	124	1"-8	3.3
	RSC-152			51	20.3	104	149	1"-8	4.1
	RSC-154	101		20.3	205	200	1"-8	5.0	
	RSC-156	152		20.3	308	271	1"-8	6.8	
	RSC-158	203		20.3	411	322	1"-8	8.2	
	RSC-1510	254		20.3	516	373	1"-8	9.5	
	RSC-1512	305		20.3	619	423	1"-8	10.9	
	RSC-1514	356		20.3	723	474	1"-8	11.8	
	RSC-251	25 (232)	26	33.2	86	139	1 1/2"-16	5.9	
	RSC-252		50	33.2	166	165	1 1/2"-16	6.4	
	RSC-254		102	33.2	339	215	1 1/2"-16	8.2	
	RSC-256		158	33.2	525	273	1 1/2"-16	10.0	
	RSC-258		210	33.2	697	323	1 1/2"-16	12.2	
	RSC-2510		261	33.2	867	374	1 1/2"-16	14.1	
	RSC-2512		311	33.2	1033	425	1 1/2"-16	16.3	
	RSC-2514		362	33.2	1202	476	1 1/2"-16	17.7	
	RSC-308	30(295)	209	42.1	880	387	—	18.1	
	RSC-502	50 (498)	51	71.2	362	176	—	15.0	
■	RSC-504		101	71.2	719	227	—	19.1	
■	RSC-506		159	71.2	1131	282	—	23.1	
▲	RSC-5013		337	71.2	2399	460	—	37.6	
▲	RSC-756	75 (718)	156	102.6	1601	285	—	29.5	
▲	RSC-7513		333	102.6	3417	492	—	59.0	
▲ ●	RSC-1004	100 (933)	102	133.3	1355	204	—	33.1	
▲ ★	RSC-1006		168	133.3	2239	357	—	59.0	
▲ ★	RSC-1008		203	133.3	2709	357	—	59.0	
▲ ★	RSC-10010		260	133.3	3466	449	—	72.6	

	焊提把 Weldable
	吊環螺絲 Eyebolt
	活動提把 Removable strap handles
	螺牙式活動提把 Thread

提把型式 Handle type	
(S) : 標準配件 standard equipped	
(O) : 選配 option	
● 焊提把 Weldable	
★ 吊環螺絲 Eyebolt	
▲ 活動提把 Removable strap handles	
■ 螺牙式活動提把 Thread	



RSC-25噸 復軌實例應用
RSC-25 ton rail way application



RSC & 泵浦特殊訂製
RSC & Pump -specific purpose

*RSC-50油壓缸具不可拆卸溝槽墊塊且無外螺牙
RSC-50 cylinder has non-removable grooved saddle and no collar thread.