

FEATURES:

- Hydraulic operated pump to drive crimping head, cutting heads and punching head including high pressure hose and coupler plug.
- PT3/8" screw thread, the oil number is Shell Tellus T 15,which must be changed every half year



Item.No:CP-180B	
Type	hand
Max output pressure	70MPa
Output of the oil	1.5cc
Capacity of oil :	185cc
Direction of piston	single
Weight:	approx.6kg
Measurement (LxWxH):	350x120x130mm



Item.No:CP-390		
Type	hand	
Max output pressure	Low pressure:	2MPa
	high pressure:	70MPa
Output of the oil	Low pressure:	4cc
	high pressure:	1cc
Capacity of oil :		390cc
Direction of piston		double
Weight:		approx.4.6kg
Measurement (LxWxH):		400x105x155mm



Item.No:CP-700		
Type	hand	
Max output pressure	Low pressure:	2MPa
	high pressure:	70MPa
Output of the oil	Low pressure:	11cc
	high pressure:	1.4cc
Capacity of oil :		940cc
Direction of piston		double
Weight:		approx.9kg
Measurement (LxWxH):		510x140x150mm



Item.No:CP-700AL		
Type	hand	
Max output pressure	Low pressure:	2MPa
	high pressure:	70MPa
Output of the oil	Low pressure:	11cc
	high pressure:	1.4cc
Capacity of oil :		900cc
Direction of piston		double
Weight:		approx.9kg
Measurement (LxWxH):		510x140x150mm