KORT



Hydraulic cutting head

1. Cut copper flat wire of transformer

2. Closed blade design for smoother cutting


3. C-type opening for easy access to the fitting

4. The exact cutting capacity depends on the type of cable or rope











Model	P-40
Output Force	6T
Rated Pressure	700bar
Cutting Capacity	Max.Ø40mm flat copper wire
Weight	3kg
Packing	Canvas Bag



Model	P-30C
Output Force	4.5T
Rated Pressure	700bar
Cutting Capacity	Max.300mm ² single core cable
	Max.240mm ² ACSR
Weight	3kg
Packing	Canvas Bag

Hydraulic cutting head Features:

- 1. Flip top style for easy access to the fitting
- 3. Powered by single acting hydraulic pump
- 2. Interlocking closed cutting head (PC-50)/ Plug pin style (PC-45, PC-55)
- 4. The exact cutting capacity depends on the type of cable or rope




Model	P-45
Output Force	6t
Rated Pressure	700bar
Cutting Capacity	Max.: Ø45mm Cu/Al/ACSR
	Max.: Ø20mm steel bar
Weight	3.8kg
Packing	Canvas Bag



P-50
6t
700bar
Max.: Ø50mm Cu/Al
2.3kg
Canvas Bag



Model	P-55
Output Force	12t
Rated Pressure	700bar
Cutting Capacity	Max.: Ø55mm Cu/Al/ACSR
	Max.: Ø22mm steel bar
Weight	4.5kg
Packing	Canvas Bag



- 1. With handle for easier operation
- 2. Powered by single acting hydraulic pump
- 3. For cutting copper and aluminum cables with light weight steel armored (depending on cable type)






Hydraulic cutting head



	Model	P-85
	Output Force	6t
	Rated Pressure	700bar
	Cutting Capacity	Max.: Ø85mm Cu/Al
		Max.: 3x185 mm² armored cable
	Weight	4.8kg
	Packing	Canvas Bag

Model	P-105
Output Force	12t
Rated Pressure	700bar
Cutting Capacity	Max.: Ø105mm Cu/Al
	Max.: 3x300mm² armored cable
Weight	10kg
Packing	Plastic Case







Hydraulic cutting head

- 1. Cut armored Cu/Al cable
- 2. Flip top cutting head for easy access to the cable

Model	P-120
Output Force	10t
Rated Pressure	700bar
Cutting Capacity	Max.: Ø120mm armored Cu/Al
Weight	11kg
Packing	Plastic Case

1. Cut large diameter Cu/Al cable or armored cable

Model	P-120C
Output Force	12T
Rated Pressure	700bar
Cutting Capacity	Max. Ø120mm armored Cu/Al
Weight	12kg
Packing	Steel Case

