

SWR&SWRM Series

Maximum Spread Force:

14 ton

Tip Clearance / Max. Spread:¹⁾

6 / 81 mm

Maximum Operating Pressure:

700 bar

1)Using Stepped block.

SWR-40 & SWRM-8 法蘭撐開器

Hydraulic Spreader

● 僅需0.24(6mm)的間隙。

● 自動回縮。

● 獨特連結設計：無首階彎曲及防滑設計。

※Only requests an access gap of 0.24" (6mm).

※Automatic mechanical retraction.




※Unique interlocking: no first step bending and risk of slipping out of joint.

型號 Model No.	最大撐開力 Max. Spread Force ton (kN)	尖端空隙 Tip clearance mm	最大撐開 Max. Spread mm	總油量 Oil Capacity c.c	重量 Weight kg
SWR-40	14 (125)	6	81	78	7.1
SWR-401	14.5 (145)	6	81	152	8.0
SWRM-8	8 (72)	6	81	—	6.5


尺寸
Dimension(mm)



SWR-40



標準配件
Equipped fitting





SWRSB1
安全墊塊
Safety Block


SWRFSB
階梯墊塊
Stepped Block



SWRM-8



標準配件
Equipped fitting





SWRSB1
安全墊塊
Safety Block


SWRFSB
階梯墊塊
Stepped Block



SWR-401



標準配件
Equipped fitting



SWRSB1
安全墊塊
Safety Block

SWRFSB
階梯墊塊
Stepped Block