KORT

Hydraulic crimping head

- U-type crimping head, sturdy and durable.
 Pin-type crimping head for easy access to the fitting.
- 3. Quick coupler for easy disassembly
- 4. Powered by single acting hydraulic pump



1. Light weight, suitable for overhead line work

Model	SCH-25
Crimping Force	25t
Stroke	20mm
Rated Pressure	700bar
Crimping Capacity	630mm ²
Weight	5.5kg
Packing	Canvas Bag







1. Flat base, keep horizontal level

Model	SCH-45
Crimping Force	45t
Stroke	20mm
Rated Pressure	700bar
Crimping Capacity	800mm²
Weight	10,6kg
Packing	Canvas Bag

Hydraulic crimping head Features:

- 1. Quick coupler for easy disassembly
- 2. Powered by single acting hydraulic pump





Model	SCH-60
Crimping Force	60t
Stroke	38.5mm
Rated Pressure	700bar
Crimping Capacity -	Cu/Al: Max. 60mm
	Steel Max. 26mm
Weight	25kg
Packing	Steel Case

Hydraulic crimping head Features:

- 1. Quick coupler for easy disassembly
- 2. Powered by single acting hydraulic pump



Hydraulic crimping head





Model	SCH-60A
Crimping Force	60t
Stroke	38.5mm
Rated Pressure	700bar
	Cu/Al: Max, 60mm
Crimping Capacity	Steel: Max. 26mm
Weight	20kg
Packing	Steel Case

Double action hydraulic crimping head Features:

- 1. Double action cylinder makes piston fast retraction
- 2. Quick coupler for easy disassembly
- 3. Powered by double acting hydraulic pump

SCH-100

Hydraulic crimping head





Crimp overhead line ACSR, strain clamps for 110kV and underground cable sleeves for 220kV

Model	SCH-100
Crimping Force	100t
Stroke	22mm
Rated Pressure	700bar
Crimping Capacity	Cu/Al; Max. 76mm
	Steel: Max. 36mm
Weight	31kg
Packing	Steel Case

SCH-200

Hydraulic crimping head





1. Crimp overhead line strain clamps and splicing sleeves for 500kV and underground cable sleeve for 220kV.

Model	SCH-200
Crimping Force	200t
Stroke	40mm
Rated Pressure	700bar
Crimping Capacity	Cu/Al: Max, 100mm
	Steel: Max. 50mm
Weight	85kg
Packing	Steel Case

08