

Hydraulic crimping head

1. U-type crimping head, sturdy and durable.
2. Pin-type crimping head for easy access to the fitting
3. Quick coupler for easy disassembly
4. Powered by single acting hydraulic pump

● **SCH-25**

Hydraulic crimping head



1. Light weight, suitable for overhead line work

Model	SCH-25
Crimping Force	25t
Stroke	20mm
Rated Pressure	700bar
Crimping Capacity	630mm ²
Weight	5.5kg
Packing	Canvas Bag

● **SCH-45**

Hydraulic crimping head



1. Flat base, keep horizontal level

Model	SCH-45
Crimping Force	45t
Stroke	20mm
Rated Pressure	700bar
Crimping Capacity	800mm ²
Weight	10.6kg
Packing	Canvas Bag

Hydraulic crimping head Features:

1. Quick coupler for easy disassembly
2. Powered by single acting hydraulic pump

● **SCH-60**

Hydraulic crimping head



Model	SCH-60
Crimping Force	60t
Stroke	38.5mm
Rated Pressure	700bar
Crimping Capacity	Cu/Al: Max. 60mm Steel Max. 26mm
Weight	25kg
Packing	Steel Case

Hydraulic crimping head Features:

1. Quick coupler for easy disassembly
2. Powered by single acting hydraulic pump

● **SCH-60A**

Hydraulic crimping head



Model	SCH-60A
Crimping Force	60t
Stroke	38.5mm
Rated Pressure	700bar
Crimping Capacity	Cu/Al: Max. 60mm Steel: Max. 26mm
Weight	20kg
Packing	Steel Case

Double action hydraulic crimping head Features:

1. Double action cylinder makes piston fast retraction
2. Quick coupler for easy disassembly
3. Powered by double acting hydraulic pump

● **SCH-100**

Hydraulic crimping head



1. Crimp overhead line ACSR, strain clamps for 110kV and underground cable sleeves for 220kV

Model	SCH-100
Crimping Force	100t
Stroke	22mm
Rated Pressure	700bar
Crimping Capacity	Cu/Al: Max. 76mm Steel: Max. 36mm
Weight	31kg
Packing	Steel Case

● **SCH-200**

Hydraulic crimping head



1. Crimp overhead line strain clamps and splicing sleeves for 500kV and underground cable sleeve for 220kV

Model	SCH-200
Crimping Force	200t
Stroke	40mm
Rated Pressure	700bar
Crimping Capacity	Cu/Al: Max. 100mm Steel: Max. 50mm
Weight	85kg
Packing	Steel Case