



Model 25GX

Single stage cylinder regulator

Applications:

- Heavy duty, large, strong regulator for the professionals

Features:

- Restyled and redesigned regulator based on 825 model
- Standardized ¼ NPT gauges, inlet and outlet parts
- New ergonomic adjusting knob
- Twist lock Ø 63 mm pressure gauges
- Enough flow to cut up to 400 mm steel
- Side entry only
- These model numbers will replace the analogous for 825 models



25GX-10-OX

MODEL NO.	GAS	MAX INLET PRESSURE (bar)	DELIVERY PRESSURE (bar)	MAX AIR FLOW (m3/h)	SUPPLY PRESSURE GAUGE (bar)	DELIVERY PRESSURE GAUGE (bar)
25GX-1.5-AC	Acetylene	25	0-1.5	52	0-40	0-2.5
25GX-4-LP	Propane	25	0-4	25	0-40	0-6
25GX-4-OX	Oxygen	230	0-4	112	0-315	0-6
25GX-4 *	Argon, CO2, Nitrogen, Air, Helium, Hydrogen, Methane	230	0-4	112	0-315	0-6
25GX-AD-4 *	Helium, Hydrogen	230	0-4	112	0-315	0-6
25GX-10-OX	Oxygen	230	0-10	170	0-315	0-16
25GX-10 *	Argon, CO2, Nitrogen, Air, Helium, Hydrogen, Methane	230	0-10	170	0-315	0-16
25GX-AD-10 *	Helium, Hydrogen	230	0-10	170	0-315	0-16
25GX-15-OX	Oxygen	230	0-15	275	0-315	0-25
25GX-15 *	Argon, CO2, Nitrogen, Air, Helium, Hydrogen, Methane	230	0-15	275	0-315	0-25
25GX-AD-15 *	Helium, Hydrogen	230	0-15	275	0-315	0-25

- The regulator is available for all the listed gases. When ordering always specify gas