

Model 801D-F. Flowmeter regulator

Applications:

- ▶ Ideal for all MIG/TIG welding applications

Features:

- ▶ Conform to ISO 2503
- ▶ Accurate pressure compensated design flowmeter for precise flow
- ▶ Flowmeter with easy to read polycarbonate outer tube cover for strength and 360° visibility
- ▶ Factory preset outlet pressure at 3,5 bar
- ▶ Forged brass body for maximum strength
- ▶ Maximum inlet pressure 230 bar
- ▶ B version fitted with black bonnet and black gauge case
- ▶ Temperature Range: -20 +60 °C
- ▶ Leak rate: max 10 cmq/h, according to ISO 9090
- ▶ Weight: 1.5 Kg
- ▶ Bonnet in Zama 15
- ▶ Diaphragm in Neoprene
- ▶ Valve seat in PTFE (Teflon)



801DB-30-F

MODEL NO.	GAS	MAX INLET PRESSURE (bar)	FLOW (Lpm)	SUPPLY PRESSURE GAUGE (bar)	FLOWMETER (Lpm)
801D-15-F-AR/CD 801DB-15-F-AR/CD	Argon / CO ₂	230	0-15	0-315	0-15
801D-30-F-AR/CD 801DB-30-F-AR/CD	Argon / CO ₂	230	0-30	0-315	0-30
801D-20-F-FG 801DB-20-F-FG	Formier Gas	230	0-20	0-315	0-20
801D-50-F-FG 801DB-50-F-FG	Formier Gas	230	0-50	0-315	0-50

