

Concrete Vibrator

Concrete Vibrator Handy Type / Engine Type

Concrete Vibrator (Handy Type)



Specifications

M A K E	MIKASA
M O D E L	MSX-32
Vib.head dia. X shaft length (mm)	32X780
Inner shaft dia. (mm)	7.7
Rubber casing dia. (mm)	25
amplitude (mm)	1.9
Vibration (Hz/V.P.M)	200~258/12,000~15,500
Power Source	280W 220V/single
total weight (kg)	4.7

Concrete Vibrator (External Type)



Specifications


M A K E	MIKASA
M O D E L	MGZ-F100A
Dimensions [LXW] (mm)	400X78
Plate size (mm)	78X100
Vibration (Hz/V.P.M)	166~200/10,000~12,000
Power Source	280W 220V/single
Weight with 4m cable (kg)	4.3

Concrete Vibrator (Engine & Motor Type)



Specifications For Vibrator Head

M O D E L	GH-32B	GH-38B
Vib.head dia. X length (mm)	32X520	38X480
Rubber hose (m)	4 · 5 · 6	
Flexible shaft dia (mm)	9.5	
amplitude (mm)	1.8	
Vibration (Hz/V.P.M)	15~208/9,000~12,500	
Weight with cable (kg)	4m	12
	6m	16
		12.5
		16.5



Specifications For Engine Drive Units

M O D E L	GE-5LV
Engine	Robin EH17D
Output rating (Max kW/PS)	3.7/5.0
Weight (kg)	24