

LH 180 : Handheld hydraulic breaker (Hex28x152) (1 1/8x6)

1801 3443 37


[Create PDF sheet](#)
[Request information](#)

PT. Atlas Copco Indonesia

+62 21 7801008

[Send an email](#)

QUICK LINKS

[Atlas Copco Print Shop](#)

[Atlas Copco Multimedia Gallery](#)

[Product information](#)

[Photos & Video](#)

[Leaflets](#)

Lightweight, multi-purpose breakers used to break brickwork, frozen soil, asphalt, concrete, as well as for tamping and compaction. The breakers are popular with contractors and rentals for indoor and outdoor renovation and demolition jobs, and are the preferred choice for major railroad companies in tie tamping applications.

Features & benefits

Low noise levels

Slim design

High power to weight ratio

Applications

Medium and hard materials as asphalt and concrete

Technical data

Units: [Metric](#) [Imperial](#)

Technical Specifications	
Weight, incl. hoses	19.5 kg
Breaker Version	Standard
Shank Size (mm)	25x108
Shank Size (inch)	1x4 1/4
Length	650 mm
Oil flow	20 l/min
Working pressure	95 - 110 bar
Back Pressure, max	10 bar
Impact Rate	1400 blows/min
Vibration level 3 axes (ISO 28927-5), 10 lpm*	15.1 m/s ²
Sound power level guaranteed, L _w (2000/14/EC)*	106 dB(A)
Sound pressure level (ISO 11203)* L _p , r=1m	93 dB(A)
EHMA class	C

Product views



Handheld Hydraulic Equipment – English - [Download](#)
Handheld Hydraulic Equipment – Swedish - [Download](#)
Handheld Hydraulic Equipment – French - [Download](#)
Handheld Hydraulic Equipment – German - [Download](#)
Handheld Hydraulic Equipment – Spanish - [Download](#)
Handheld Hydraulic Equipment – Italian - [Download](#)
Handheld Hydraulic Equipment – Dutch - [Download](#)
Handheld Hydraulic Equipment – Hungarian - [Download](#)
Handheld Hydraulic Equipment – Russian - [Download](#)
Handheld Hydraulic Equipment – Polish - [Download](#)
Handheld Hydraulic Equipment – Turkish - [Download](#)
Handheld Hydraulic Equipment – US English - [Download](#)