

TEX 140PS: Pneumatic breaker (Hex 22x82,5) (7/8x3 1/4)

8461 0223 30


[Create PDF sheet](#)
[Request information](#)

PT. Atlas Copco Indonesia

+62 21 7801008

[Send an email](#)

QUICK LINKS

[Atlas Copco Print Shop](#)

[Atlas Copco Multimedia Gallery](#)

[Product information](#)
[Photos & Video](#)

TEX 140-280 is a range of light and medium sized breakers. They are ideal for service jobs and general demolition, but not for use in very hard materials or heavily reinforced concrete.

Features & benefits

- Solid Body concept
- Noise-reduction
- SOFSTART™ two-step trigger
- Rotating air inlet swivel
- Integrated lubricator
- Air cushioned piston

Applications

- Service jobs
- General demolition
- For use in soft and medium material

Technical data

Units: [Metric](#) [Imperial](#)

Technical Specifications	
Breaker type	Standard
Breaker Version	Silenced
Shank Size (mm)	Hex 22x82.5
Shank Size (inch)	Hex 7/8x3 1/4
Weight	15.5 kg
Length	590 mm
Air consumption	25 l/s
Impact Rate	1530 blows/min
Vibration level 3 axes (ISO 28927-10)	15.2 m/s²
Sound power level guaranteed, Lw (2000/14/EC)*	104 dB(A)
Sound pressure level (ISO 11203)** Lp, r=1m	91 dB(A)

Product views

