

PUMPMASTER 2 ACCESSORIES, OTHER MOBILE OIL DISPENSERS
PUMPMASTER 2 ACCESSORIES

360 102


360 102 Wall bracket
360 120 Floor bracket

360 120



360 001


BUNG ADAPTORS 2" (M) CONNECTION FOR DRUM AND TANKS BUNG OPENINGS
360 000 Bung adaptor for PM2 3:1 pumps
 Pump tube outside diameter: 34 mm.

360 001 Bung adaptor for PM2 1:1 pumps
 Pump tube outside diameter: 52 mm.

367 000


SUCTION ASSEMBLIES AND SUCTION HOSES
 Suction assemblies for wall mounted stub pumps. Assemblies include Ø 42 suction tube with foot valve, height adjustable 2" bung adaptor and 2 m x 3/4" rubber connection hose.

367 000 Suction assembly for 1.000 l IBC and 205 l drums
 1.060 mm suction tube.

367 003 Suction assembly for tanks
 1.600 mm suction tube.

367 011 spring reinforced transparent suction hose
 For 205 l drums and 1.000 l IBC. 3 m x 3/4".


367 012 spring reinforced transparent suction hose with foot valve
 For 205 l drums and 1.000 l IBC. 3 m x 3/4", includes foot valve.

367 102 Pump suction kit
 Includes suction assemble 367 000 and pump bracket 360 102.


367 011



369 910


HOSE CONNECTION KIT
362 910 PM2 pump connection kit
 1 m x 1/4" air hose 246 010, one 1/2" BSP (M) x 1/4" BSP (M) connection adapter 945 516, 1 m x 1/2" oil hose with 1/2" BSP (MM) fittings, one automatic quick air coupling 1/4" BSP (F) 253114 and one quick air connector 1/4" BSP (M).

609 007


PRESSURE RELIEF VALVE

SAMOA pumps include a 1/4" plug that can be removed and replaced with a pressure relief valve.

609 007 Pressure relief valve
 Opens at approx. 60 bar. Possibility to connect either a 1/4" hose with a clamp or a hose with 1/8" BSP (F) fitting as oil return live.

OTHER MOBILE OIL DISPENSERS

PRESSURIZED LUBRICANT DISPENSERS 25 LITRES

Mobile unit for dispense viscous lubricants. Includes a 25 l container that must be pressurized using a tire inflator at maximum 7 bar (100 psi). Includes safety valve and 1,5 m delivery hose with oil gun.

324 000 Pressurized lubricant dispenser, 25 litres.
324 010 Pressurized lubricant dispenser, 25 litres with meter.

SELF CONTAINED AIR OPERATED LUBRICANT DISPENSER 25 LITRES

Mobile unit to dispense viscous lubricants. Includes a 25 l capacity tank, a 2:1 pneumatic pump, oil meter at pump outlet, 1,5 m delivery hose and oil gun with non-drip tip.

327 020 Self contained air operated lubricant dispenser with meter, 25 litres.

SELF CONTAINED HAND OPERATED LUBRICANT DISPENSERS 25 LITRES

Mobile unit to dispense viscous lubricants. Includes a 25 l capacity tank, a hand pump and a 1,5 m delivery hose with angled spout.

325 000 Self contained hand operated lubricant dispenser, 25 litres.
325 010 Self contained hand operated lubricant dispenser with meter, 25 litres. Includes in line meter at the pump outlet.

SELF CONTAINED HAND OPERATED LUBRICANT DISPENSERS 70 LITRES

Mobile unit to dispense viscous lubricants. Includes a 70 l capacity tank, a hand pump and a 1,5 m delivery hose with angled spout.

326 000 Self contained hand operated lubricant dispenser, 65 litres.
326 010 Self contained hand operated lubricant dispenser with meter, 65 l
 Includes in line meter at the pump outlet.

424 172 - 424 152

482 200

425 150.002

428 243

Mobile and portable units to fit 18, 20, 50 and 185 kg drums.



Part No.	APPLICATION	PUMP	DRUM COVER	FOLLOWER PLATE	DELIVERY HOSE	GREASE GUN WITH Z-SWIVEL	TROLLEY
424 150	Mobile unit, 12,5 to 18 kg (1)	404 100	418 013	-	2 m x 1/4" 412 102	413 080	430 000
424 152	Mobile unit, 20 kg (1)	404 100	418 002	-	2 m x 1/4" 412 102	413 080	430 000
424 170	Portable unit, 12,5 to 18 kg (1)	404 100	418 013	-	2 m x 1/4" 412 102	413 080	-
424 170.800	Portable unit, 12,5 to 18 kg (1)	404 100	418 013	417 001	2 m x 1/4" 412 102	413 080	-
424 172	Portable unit, 20 kg (1)	404 100	418 002	-	2 m x 1/4" 412 102	413 080	-
424 172.710	Portable unit, 20 kg (1)	404 100	418 002	417 001	2 m x 1/4" 412 102	413 080	-
482 200	Mobile unit, 12,5 to 20 kg (2)	404 100	-	-	2 m x 1/4" 412 102	413 080	480 021
425 150	Mobile unit, 50 kg drum	407 200	418 004	-	3 m x 1/4" 412 103	413 080	431 000
425 150.002	Mobile unit, 50 kg drum	407 200	418 004	417 002	3 m x 1/4" 412 103	413 080	431 000
425 290	Mobile unit, 50 kg drum	407 200	418 004	-	2 m x 1/4" 412 102	413 080	430 000
482 500	Mobile unit, 50 kg drum (3)	407 200	-	-	3 m x 1/4" 412 103	413 080	480 050
428 243	Mobile unit, 185 kg drum	409 200	418 006	417 004	4 m x 1/4" 412 104	413 080	432 000
428 262	Stationary unit, 185 kg drum	409 200	418 006	417 004	4 m x 1/4" 412 104	413 080	-

(1) Includes carrying handle 741 602.

(2) Shielded unit. Includes base with 4 castors.

(3) Shielded unit. Includes base with 2 wheels and 2 castors.

Not included options:

239 000: 1/4" BSP (MM) connection adaptor.

240 500: Air filter and pressure regulator, 0-12 bar, 1/4" BSP (FF).

417 001: Follower plate 298 - 260 mm. For 12,5 and 18 kg pails.

417 002: Follower plate 370 - 330 mm. For 50 kg standard diameter drums.

417 003: Follower plate 405 - 360 mm. For 50 kg large diameter drums.

417 005: Follower plate 340 - 300 mm. For 20 kg pails.

411 100: In-line grease meter for grease control gun.

PUMPMASTER 3+3 60:1 RATIO PUMP KITS



429 800

429 810 Pumpmaster 3+3 60:1 ratio pump kit for 50 kg drums
Includes 60:1 ratio pump for 50 kg drums 402 000 with drum cover for 50 kg drum 418 004 and hose connection kit 412 920.

429 800 Pumpmaster 3+3 60:1 ratio pump kit for 185 kg drums
Includes 60:1 ratio pump for 185 kg drums 402 025 with drum cover for 185 kg drum 418 006, follower plate for 185 kg drums 417 004 and hose connection kit 412 920.



453 602



426 243



486 500



423 150

PUMPMASTER 3+3 60:1 RATIO PACKAGES FOR 185 KG AND 50 KG DRUMS

	PUMP AND HOSE REEL PACKAGE FOR 185 KG DRUMS	MOBILE PACKAGE FOR 185 KG DRUMS	MOBILE PACKAGE FOR 50 KG DRUMS	MOBILE PACKAGE FOR 50 KG DRUMS
PART No.	453 602	426 243	486 500	423 150
PUMP	402 025	402 025	402 000	402 000
DRUM COVER	418 006	418 006	-	418 013
FOLLOWER PLATE	417 004	417 004	-	-
HOSE CONNECTION KIT	412 920	-	-	-
GREASE GUN WITH Z-SWIVEL	413 080	413 080	413 080	413 080
DELIVERY HOSE	15 m Hose reel 504 301	4 m x 1/4" 412 104	3 m x 1/4" 412 103	3 m x 1/4" 412 103
DRUM TROLLEY	-	432 000	480 050 ⁽¹⁾	431 000

(1) Shielded unit. Includes base with 2 wheels and 2 castors.

Not included options:

- 239 001:** 1/4" BSP (M) - 3/8" BSP (M) connection adaptor.
- 240 500:** Air filter and pressure regulator, 1/4" BSP (FF).
- 360 111:** Hose reel pivoting bracket.
- 360 127:** Control gun holder and drip tray.
- 417 002:** Follower plate 370 - 330 mm. For 50 kg standard diameter drums.
- 417 003:** Follower plate 405 - 360 mm. For 50 kg large diameter drums.
- 411 100:** In line grease meter for grease control gun.

486 200 - 423 020

PUMPMASTER 3+3 60:1 RATIO PACKAGES FOR 18 KG AND 20 KG PAILS

02
GREASE PUMPS



	MOBILE PACKAGE FOR 20 KG PAILS	PORTABLE PACKAGE FOR 18 KG PAILS
PART No.	486 200	423 020
PUMP	402 050	402 050
DRUM COVER	-	418 013
FOLLOWER PLATE	-	417 001
GREASE GUN WITH Z SWIVEL	413 080	413 080
DELIVERY HOSE	2 m x 1/4" 412 102	2 m x 1/4" 412 102
DRUM TROLLEY	480 021 ⁽¹⁾	-

(1) Shielded unit. Includes base with 4 castors.

424 060

MOBILE EXTRUSION UNIT FOR 12-20 KG PAILS



Mobile unit specially designed for its use with hard to pump sticky and high viscosity greases (up to NLGI3).

The pump's lower end is fixed to an inductor plate and the pump is mounted to a pneumatic piston that elevates the pump for replacing an empty pail. The pneumatic piston also acts when the pump is in use, pushing the inductor plate against the grease, aiding the pump prime, making possible to pump very high viscosity grease. Follower plate increases productivity as it eliminates air pockets and contributes to maintain grease free from dirt in industrial environments. The air cylinder is controlled with a valve located on the top of the inductor post and it includes a pressure regulator to adjust the downward pressure.

The unit includes a PM 3+3 60:1 pressure ratio pump and it is mounted to a rolling base with 4 wheels, two of them with brake.

424 060 Mobile extrusion unit

Includes 3 m high pressure hose and a grease control gun with Z-swivel and hydraulic nozzle.

424 061 Mobile extrusion unit

Same as model 424 060 but with no outlet hose and grease control gun.

Air filter and regulator (PN 240 500) is non included option.

Not included options:

239 001: 1/4" BSP (M) - 3/8" BSP (M) connection adaptor.

240 500: Air filter and pressure regulator, 1/4" BSP (FF).

417 001: Follower plate 298 - 260 mm. For 12,5 and 18 kg pails.

417 005: Follower plate 340 - 300 mm. For 20 kg pails.

411 100: In line grease meter for grease control gun.

418 004 - 417 003

DRUM COVERS AND FOLLOWER PLATES

Drum covers. Very solid construction. With 2" BSP (F) bung opening.



PART No.	DRUM TYPE	DRUM EXTERNAL DIAMETER (MIN. - MAX.)
418 013	12,5 to 18 kg pails	265 - 310 mm
418 002	20 kg pails	285 - 330 mm
418 016	50 kg drums	350 - 395 mm
418 004	50 kg drums	360 - 405 mm
418 006	185 kg drums	565 - 610 mm

Follower plates eliminate air pockets and aid pump prime. Rubber flange minimizes waste. With handle for removing from empty drums.

PART No.	DRUM TYPE	DRUM EXTERNAL DIAMETER (MIN. - MAX.)
417 006	12,5 kg pails	190 - 260 mm
417 001	12,5 to 18 kg pails	260 - 298 mm
417 005	20 kg pails	300 - 340 mm
417 002	50 kg drums	330 - 370 mm
417 003	50 kg drums	360 - 405 mm
417 004	185 kg drums	550 - 590 mm

430 000 - 431 000 - 432 814 - 432 000

DRUM TROLLEYS



430 000 Trolley for 20 kg pails

Two wheel trolley with tubular frame for 20 and 50 kg drums.

431 000 Trolley for 50 and 20 kg drums

Four wheel trolley with tubular frame.

431 001 Trolley for 50 and 20 kg drums

Two wheel and two front rubber pads trolley with tubular frame.

480 050 Mobile protective drum cabinet, 50 kg

480 021 Mobile protective drum cabinet, 20 kg

432 000 Trolley for 185 kg drum.

Two solid rubber wheels and one swivelling rubber wheel with brake. A hose reel and a pump can be, mounted using optional bracket.

360 134 Pump bracket

For mounting a short pump to trolley 432 000.

360 135 Hose reel bracket

For mounting a hose reel to trolley 432 000.

432 814 Heavy Duty trolley for 185 kg drum

Two 260 mm front tires and one swivelling solid rubber wheel with brake. A hose reel can be, mounted using optional bracket.

360 113 Hose reel bracket.

For mounting a hose reel to trolley 432 814.