

PH302 – Sewer Jet 3000 PSI

 polyhose.com/products/thermoplastic-hose/ph-302-sewer-jet-3000-psi/

Application

Standard Sewer Cleaning vehicles and cleaning equipments

Heavy duty construction for optimum cut and wear resistance. Bonded tube and cover. Available in long lengths with a special cover, resistant to microbiological degradation. Lightweight compared to conventional rubber alternatives and increased lifetime.



Code	Dash size	DN	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Part#			inch	mm	inch	mm	psi	bar	psi	bar	mm	inch
PH302-6	-6	10	3/8	9.5	0.650	16.5	3000	210	7500	525	75	3.0
PH302-8	-8	12	1/2	12.7	0.880	22.4	3000	210	7500	525	100	4.0
PH302-12	-12	20	3/4	19.0	1.150	29.21	3000	210	7500	525	125	5.0
PH302-16	-16	25	1	25.4	1.475	37.46	3000	210	7500	525	160	6.4
PH302-20	-20	32	1.1/4	31.8	1.830	46.48	3000	210	7500	525	250	10.0

Applicable Standard:

Standard: ISO7751

Construction:

Core: Thermoplastic Elastomer

Reinforcement: 1 or 2 braids of synthetic fibre plus one special extra braid

Cover: Blue color – polyurethane.

Temperature Range:

Continuous: -40°C to +60°C

Copyright © Polyhose. All rights reserved. Powered by [i-Vertys](#)