

LH 270 : Handheld hydraulic breaker (Hex28x152) (1 1/8x6)

1801 3643 56



[Create PDF sheet](#)

[Request information](#)

Gizem Uzun
+90 (0) 581 0 581
[Send an email](#)

QUICK LINKS

[Atlas Copco Print Shop](#)
[Atlas Copco Multimedia Gallery](#)

[Product information](#)

[Photos & Video](#)

[Leaflets](#)

This powerful, high productivity breaker provide heavy-duty breaking in frozen soil, asphalt and reinforced concrete and are considered to be among the best in its class.

Features & benefits

- Low noise levels
- Slim design
- High power to weight ratio

Applications

Medium and hard materials as asphalt and concrete

Technical data

Units: [Metric](#) [Imperial](#)

Technical Specifications	
Weight, incl. hoses	26.5 kg
Breaker Version	Standard
Shank Size (mm)	28x152
Shank Size (inch)	1 1/8x6
Length	765 mm
Oil flow	20 - 30 l/min
Working pressure	110 - 125 bar
Back Pressure, max	15 bar
Impact rate	1350 - 1750 blows/min
Vibration level 3 axes (ISO 28927-5), 10 lpm*	19.4 m/s ²
Sound power level guaranteed, Lw (2000/14/EC)*	107 dB(A)
Sound pressure level (ISO 11203)* Lp, r=1m	94 dB(A)
E-ITMA class	C/D

Product views



- Handheld Hydraulic Equipment – English - [Download](#)
- Handheld Hydraulic Equipment – Swedish - [Download](#)
- Handheld Hydraulic Equipment – French - [Download](#)
- Handheld Hydraulic Equipment – German - [Download](#)
- Handheld Hydraulic Equipment – Spanish - [Download](#)
- Handheld Hydraulic Equipment – Italian - [Download](#)
- Handheld Hydraulic Equipment – Dutch - [Download](#)
- Handheld Hydraulic Equipment – Hungarian - [Download](#)
- Handheld Hydraulic Equipment – Russian - [Download](#)
- Handheld Hydraulic Equipment – Polish - [Download](#)
- Handheld Hydraulic Equipment – Turkish - [Download](#)
- Handheld Hydraulic Equipment – US English - [Download](#)