

Semiautomatic plastic strapping machine

Economical • Easy to operate • Reliable







The TTX is the ideal plastic strapping system for low volume users. Its simple open cabinet, bottom seal design makes it ideal for strapping bundles, cartons or coiled products.

## Easy to operate

The TTX's strapping head features cam-operated feeding, retracting and tension for easy operation. Its external tension control and setting indicators further simplify operation.



# Simplified maintenance

Constructed with electrical safety interlocks on the hinged top plate, when the TTX's top cover is opened, all power to the machine is cut off for easy troubleshooting.

# Reliable performance

The sensor controlled heat sealing mechanism ensures consistent, high-efficiency seals. Weld cooling time can be adjusted for proper sealing. Package guides ensure ideal strap placement.

### Durable

The TTX features a welded steel frame with stainless steel top plates for maximum durability.

### **Portable**

Four locking casters enable the machine to be positioned wherever needed.





## **TTX Specifications**

#### Package size:

Minimum: 2" H x 3-1/2" W (50.8 mm x 88.9 mm)

Maximum: Unlimited

**Strapping:** 1/4" 3/8", or 1/2" polypropylene on 8" x 8", or 9" x 8" ID core sizes.

Strap tension: 10-80 lbs.

Electrical requirements: 120 Volts, Single Phase, 60 Hz

Machine weight: 185 lbs.

3640 West Lake Avenue Glenview, IL 60026 1-800-323-2464 | www.signode.com