

Manual Welding Products




Tweco® Ground Clamps



SGC-500



GC-300



FGC-500

Part Number	Stock Number	Amperage Capacity	Jaw Opening	Cable Conn Capacity	English Length	Metric Length
SGC-300	9205-1230	300	2" - Depth 1-3/4" (50.8 mm - 44.4 mm)	1/2" Stud Connection	9"	228 mm
SGC-500	9205-1250	500	2" - Depth 1-3/4" (50.8 mm - 44.4 mm)	1/2" Stud Connection	9"	228 mm
GC-200	9205-1120	200	1" - Depth 3" (25.4 mm - 76.2 mm)	Ball-Point thru 1/0	6"	157 mm
GC-300*	9205-1130	300	1-1/2" - Depth 4" (38.1 mm - 101.0 mm)	Ball-Point thru 3/0	8-1/2"	216 mm
GC-300MC**	9205-1131	300	1-1/2" - Depth 4" (38.1 mm - 101.0 mm)	Ball-Point thru 3/0	8-1/2"	216 mm
GC-500	9205-1150	500	2" - Depth 5-1/4" (50.8 mm - 133.0 mm)	Ball-Point thru 4/0	10"	254 mm
FGC-200	9205-1320	200	5/8" - Depth 2" (15.9 mm - 50.8 mm)	Ball-Point thru 1/0	5"	127 mm
FGC-300	9205-1330	300	1" - Depth 3-1/2" (25.4 mm - 88.9 mm)	Ball-Point thru 3/0	7-1/4"	184 mm
FGC-500	9205-1350	500	1-1/4" - Depth 3-3/4" (31.8 mm - 95.3 mm)	Ball-Point thru 4/0	9-1/4"	234 mm

* Clamshell packaging. Sold individually or master packed in quantities of 12 each.

** Sold in Master Pack Boxed Quantities of 24.

TWECOTONG® Electrode Holders



A-316



A-732



A-14

Part Number	Stock Number	Amperage Capacity	Body Alloy	Electrode Capacity	Cable Conn Capacity	English Length	Metric Length
A-532*	9110-1101	200	Copper Alloy	thru 5/32" (4,0 mm)	Ball-Point thru 2/0	8-1/2"	216 mm
A532-MC**	9110-1109	200	Copper Alloy	thru 5/32" (4,0 mm)	Ball-Point thru 2/0	8-1/2"	216 mm
A-316*	9110-1102	250	Copper Alloy	thru 3/16" (4,8 mm)	Ball-Point thru 2/0	9-1/4"	235 mm
A316-MC**	9110-1110	250	Copper Alloy	thru 3/16" (4,8 mm)	Ball-Point thru 2/0	9-1/4"	235 mm
A-732*	9110-1103	300	Copper Alloy	thru 7/32" (5,6 mm)	Ball-Point thru 2/0	10"	254 mm
A732-MC**	9110-1111	300	Copper Alloy	thru 7/32" (5,6 mm)	Ball-Point thru 2/0	10"	254 mm
A-14	9110-1104	350	Copper Alloy	thru 1/4" (6,4 mm)	Ball-Point thru 4/0	11"	279 mm
A-14-HD	9110-1105	400	Copper Alloy	thru 1/4" (6,4 mm)	Double Ball-Point thru 4/0	12"	305 mm
A-38-HD	9110-1106	500	Copper Alloy	thru 3/8" (9,5 mm)	Double Ball-Point thru 4/0	13-1/4"	336 mm

* Clamshell packaging. Sold individually or master packed in quantities of 12 each.

** Sold in Master Pack Boxed Quantities of 24.

Tweco Cable Connectors



2-1-MPC



4-MPC

MPC SERIES POSITIVE-CAM MECHANICAL CONNECTION - ZINC PLATED TYPE CABLE & COVER SCREWS

Part Number	Stock Number	Description	Type Cable Connection	Cable Capacity	Standard Package
1-MPC	9425-1100	Complete Connection	Single Ball-Point	4, 2, 1	1 ea. Male/Female
1-MPC-1	9425-1110	Male Half	Single Ball-Point	4, 2, 1	Pkg. 2 ea. Male
1-MPC-2	9425-1120	Female Half	Single Ball-Point	4, 2, 1	Pkg. 2 ea. Female
2-MPC ‡	9425-1200	Complete Connection	Single Ball-Point	1/0, 2/0, 3/0	1 ea. Male/Female
2-MPC-MC**	9425-1201	Complete Connection	Single Ball-Point	1/0, 2/0, 3/0	1 ea. Male/Female
2-MPC-1 †	9425-1210	Male Half	Single Ball-Point	1/0, 2/0, 3/0	Pkg. 2 ea. Male
2-MPC-1-MC*	9425-1211	Male Half	Single Ball-Point	1/0, 2/0, 3/0	Pkg. 2 ea. Male
2-MPC-2 †	9425-1220	Female Half	Single Ball-Point	1/0, 2/0, 3/0	Pkg. 2 ea. Female
2-MPC-2-MC*	9425-1221	Female Half	Single Ball-Point	1/0, 2/0, 3/0	Pkg. 2 ea. Female
4-MPC ‡	9425-1400	Complete Connection	Double Ball-Point	3/0 or 4/0	1 ea. Male/Female
4-MPC-MC**	9425-1401	Complete Connection	Double Ball-Point	3/0 or 4/0	1 ea. Male/Female
4-MPC-1 †	9425-1410	Male Half	Double Ball-Point	3/0 or 4/0	Pkg. 2 ea. Male
4-MPC-1-MC*	9425-1411	Male Half	Double Ball-Point	3/0 or 4/0	Pkg. 2 ea. Male
4-MPC-2 †	9425-1420	Female Half	Double Ball-Point	3/0 or 4/0	Pkg. 2 ea. Female
4-MPC-2-MC*	9425-1422	Female Half	Double Ball-Point	3/0 or 4/0	Pkg. 2 ea. Female
2-1-MPC	9425-1140	Whip Connection	Single Ball-Point	4, 2, 1, 1/0	Pkg. 2 ea.

* Sold in Master Pack Boxed Quantities of 48.

** Sold in Master Pack Quantities of 24.

† Clamshell packaging. Sold individually or master packed in quantities of 24 each.

‡ Clamshell packaging. Sold individually or master packed in quantities of 12 each.