



**CERTS ASSURED LTD**

## Low Profile Pad Cylinders

Capacity: 5 - 150 tonnes.

Stroke: 6 - 16mm.

Maximum Pressure: 700 Bar.

Hydraulic Coupler: TBC 381F(PT3/8).

TECPOS low profile cylinders are designed for use where there is a minimum of clearance for insertion of Cylinders

From 10 to 150 tones capacity single-acting spring return.



### Understanding the Model No: TSLC-1011

**T** - TECPOS

**SLC** - Low Profile Cylinder

**10** - Capacity, 10ton

**11** - Stroke, 11mm

### Model:

### Dimensions

Model	Cyl. Cap.	Stroke	Cyl. Effective Area	Oil Cap.	Retracted Height	Extended Height	Cyl. Out Dia.	Cyl. Bore Dia.	Piston Rod Dia.	Plunger to Base	Cylinder Dims	Base to inlet port	Weight
	(tons)	(mm)	(cm <sup>2</sup> )	(cc)	A	B	C	D	E	F	G	H	(kgs)
TSLC-56	5	6	6.16	3.7	40	46	60	28	25	22	42	21	0.8
TSLC-1011	10	11	15.2	16	45	56	85	44	38	29	56	21	1.5
TSLC-2011	20	11	28.3	31	52	63	102	60	54	42	76	21	2.7
TSLC-3013	30	13	41.85	53	59	72	115	73	64	48	95	21	4.2
TSLC-5016	50	16	60.8	99	67	83	139	88	75	58	114	21	6.9
TSLC-7516	75	16	103.87	164	79	95	165	115	85	70	140	21	11
TSLC-10016	100	16	126.7	203	86	102	180	127	95	78	152	25	14.7
TSLC-15016	150	16	201	317	100	116	215	160	115	97	190	24	25

