

## Strapping Dispensers, Tensioners and Sealers Cont.

### Manual Regular Duty Steel Sealers



Part No.	Description	Strap Width	Strap Gauge Range
580085	Tensioner - Feedwheel, Type with Unlimited Take-up	3/8" - 3/4"	0.015" - 0.025"
580087	Sealer - Front Action, Double Notch Down Cut	1/2"	0.015" - 0.023"
580088	Sealer - Front Action, Double Notch Down Cut	5/8"	0.015" - 0.023"
580089	Sealer - Front Action, Double Notch Down Cut	3/4"	0.015" - 0.023"

### Regular-Duty Tensioners and Sealers

There are three types of tensioners: Conventional, Pusher, and Windlass

Some examples include:

Sealers: For light to medium-duty applications sealer handles are designed with front action handles which are perpendicular to the load. For Heavy-duty applications sealer handles are designed with side action handles for greater leverage.



Part No.	Description	Strap Width	Strap Gauge Range
0523712	Tensioner - Conventional Feedwheel Type, Non-push Type	3/8" - 3/4"	0.015" - 0.025"
0523713	Sealer - Front Action, Double Notch Down Cut	1/2"	0.015" - 0.023"
0523714	Sealer - Front Action, Double Notch Down Cut	5/8"	0.015" - 0.023"
0523715	Sealer - Front Action, Double Notch Down Cut	3/4"	0.015" - 0.023"

### Heavy-duty Tensioners and Sealers



Part No.	Description	Strap Width	Strap Gauge Range
580096	H/D Tensioner - Feedwheel, Type with Unlimited Take-up	3/4" - 1-1/4"	0.025" - 0.044"
580101	Sealer - Side Action, Double Notch Upcut (Reverse Notch)	1-1/4"	.025" - .035"
580103	Sealer - Front Action, Double, Notch Down Cut	3/4"	0.023" - 0.031"

### Heavy-duty Tensioners and Sealers

For use with flat load applications



Part No.	Description	Strap Width	Strap Gauge Range
0523716	H.D. Feedwheel Tensioner	3/4" - 1-1/4"	0.025" - 0.031"
0523717	H.D. Steel Strap Sealer, Double Notch, Up Cut, Side Action	1-1/4"	0.025" - 0.035"
0523718	H.D. Steel Strap Sealer, Double Notch, Down Cut, Front Action	3/4"	0.023" - 0.031"
580099	H.D. Tensioner Windlass Type with Limited Take-up	3/4" - 1-1/4"	0.028" - 0.035"
580100	Sealer - Side Action, Double Notch Upcut (Reverse Notch)	3/4"	0.025" - 0.035"

### Front Action Serrated Crimp Polyester Sealer

- Symmetrical Jaws

Part No.	Strap Width	Strap Gauge Range
0544987	1/2"	0.015" - 0.030"



### Poly Strapping Tensioners and Sealers



Part No.	Description	Strap Width	Strapping Type
580135	Tensioner/Cutter - Windlass, Limited Take-Up	1/2" - 3/4"	Polypropylene
580164	H/D Tensioner/Cutter - Windlass, Limited Take-Up	1/2" - 3/4"	Poly./Polyester/Poly Cord

### Poly Strapping Tensioners and Sealers

Sealers for poly strapping are based on the type of seals they will be closing. The sealers are designed with handles which are front action that are perpendicular to the strapping for light to Heavy-duty applications or side action for Heavy-duty applications.



Seals for poly strapping are of three types:

- Snap-on semi-open seals
- Snap-on semi-open serrated seals
- Buckles



Part No.	Description	Strap Width	Strapping Type
0523720	Windlass Tensioner/Cutter	3/8" - 3/4"	Cord / Plastic
0523723	H/D Windlass Tensioner/Cutter	1/2" - 3/4"	Cord / Plastic
0578760	H/D Poly Sealer - Front Action	1/2"	Polypropylene
0578761	H/D Poly Sealer - Front Action	5/8"	Poly
0578762	R/D Tensioner/Cutter - Windlass, Limited Take-up	1/2" - 3/4"	Poly./Polyester/Poly Cord
580136	Front Action General Purpose, Poly Sealer	1/2" - 5/8"	Polypropylene
580137	Front Action General Purpose, Poly Sealer	5/8"	5/8" Polypropylene
580165	H/D Offset Poly Sealer	1/2"	Polyester / Nylon
580166	H/D Offset Poly Sealer - Front Action	5/8"	Polyester / Nylon

### Aspect Seal-less Combination Steel Strapping Tool

Part No.	Style	Strap Width	Strap Gauge Range
0530716	Regular Duty	1/2", 5/8", 3/4"	0.015" - 0.027"



### Manual Sealless Combination Tools

- Tensions, seals and cuts

Part No.	Strap Width	Strap Gauge Range
0544965	5/8"	0.015" - 0.025"
0544966	3/4"	0.015" - 0.025"
0544988	1/2"	0.015" - 0.025"



### Orgapack™ Sealless Combination Tool for Steel Strapping



Part No.	Strap Width	Strap Gauge Range
0531199	1/2"	0.015 - 0.023"
0531200	5/8"	0.015 - 0.023"
0531201	3/4"	0.015 - 0.023"
0531202	3/4"	0.022 - 0.031"
0531203	1/2" - 5/8"	0.020 - 0.040"
0531204	5/8" - 3/4"	0.035 - 0.050"

### Seal Saver Seal-less Manual Combination Strapping Tool

One Tool Does it All - For flat surfaces only.

1. Tensions
2. Seals Strap
3. Cuts Strap

A single tool tensions, seals and cuts strap - faster operation than conventional two piece methods. Seal jams are eliminated. For quick application, slack strap can be pulled up by hand. The tool has unlimited take-up. The Seal Saver Strapping joint is the strongest and most consistent in the industry, with 82% joint efficiency for the whole life of the tool. Association of American Railroads and US Government Approved.



Part No.	Strap Width	Strap Thickness	Style
580147	1/2"	0.023"	Regular Duty
580148	5/8"	0.023"	Regular Duty
580149	3/4"	0.023"	Regular Duty
580150	1/2"	0.020"	High Tensile
580151	5/8"	0.020"	High Tensile
580152	3/4"	0.020"	High Tensile

For pricing and availability, contact your local Fastenal store or visit [fastenal.com](http://fastenal.com)