

Great Plains Industries, Inc.
 5252 E. 36th St. N.
 Wichita, KS 67220
Tel: 800-835-0113
Direct: 316-686-7361
Fax: 316-686-6746
Email: gpisales@gplains.com

Oil Transfer Pumps



Our oil transfer pumps are designed for use with non-flammable fluids including: antifreeze, hydraulic fluid, non-flammable oil based solvents and oil based herbicide carriers. GPI oil pumps are available in both 115 V and 12 V models and work great with drums, bulk tanks and waste oil reserves. Durable and easy to handle, they are weatherproof with built-in easy access inlet screen & by-pass valve and 1 or 2 year warranties.

Results 1 - 5 of 5

Item #	Model	Design Type	Voltage	Mechanical Connection	Flowrate	Operating Temperature	Hose	Nozzle
142100-03	L 5016	Gerotor Gear	12 Volts DC	1 in. Inlet ¾ in. Outlet	Up to 16 qpm Up to 15 LPM	Max +140 °F Max +60 °C	8 ft 2.5 m ¾ in. diameter	¾ in. Ball Valve
142100-02	L 5132	Gerotor Gear	115/230 Volts AC	1 in. Inlet ¾ in. Outlet	Up to 8 GPM Up to 32 qpm Up to 30 LPM	Max +140 °F Max +60 °C	8 ft 2.5 m ¾ in. diameter	Ball Valve Type
142100-01	L 5116	Gerotor Gear	115/230 Volts AC	1 in. Inlet ¾ in. Outlet	Up to 4 GPM Up to 16 qpm Up to 15 LPM	Max +140 °F Max +60 °C	8 ft 2.5 m ¾ in. diameter	Ball Valve Type
118000-9	P-200-2UR	Gear	12 Volts DC	1 in. Inlet 1 in. Outlet	Up to 8 GPM Up to 32 qpm Up to 30 LPM	-20 to 125 °F -29 to 52 °C	12 ft 3.7 m 1 in. diameter	1 inch Ball Valve Nozzle
118003-11	PA-200-2UR	Gear	115 Volts AC	1 in. Inlet 1 in. Outlet	Up to 8 GPM Up to 32 qpm Up to 30 LPM	-20 to 125 °F -29 to 52 °C	12 ft 3.7 m 1 in. diameter	Ball Valve Type

Results 1 - 5 of 5