


## Hexagon and Offset Keys

### 159 Hexagon Key



<b>Application</b>	for hexagon socket head cap screws according to DIN 912		
<b>Type</b>	nickel plated, 159M-0,7 up to 1,3 black finish		
<b>Material</b>	Chrome-Vanadium 59 CrMoV 4, Code No. 1.2243		
<b>Standard</b>	according to DIN 911/ISO 2936		

Stock-No.	for DIN 912	mm	mm	g
159- 0,7		33 × 7	48	0,4
159- 0,9		33 × 11	48	0,5
159- 1		33 × 11	48	0,5
159- 1,3	M1,4	41 × 13	48	0,7
159- 1,5	M1,6 M2	46,5 × 15,5	48	1,0
159- 2	M2,5	52 × 18	48	2,0
159- 2,5	M3	58,5 × 20,5	48	4,0
159- 3	M4	66 × 23	24	5,0
159- 3,5		69,5 × 25,5	24	8,0
159- 4	M5	74 × 29	24	10,0
159- 4,5		80 × 30,5	24	15,0
159- 5	M6	85 × 33	24	18,0
159- 6	M8	96 × 38	24	30,0
159- 7		102 × 41	24	43,0
159- 8	M10	108 × 44	12	59,0
159- 9		114 × 47	12	79,0
159- 10	M12	122 × 50	12	103,0
159- 11		129 × 53	12	131,0
159- 12	M14	137 × 57	12	160,0
159- 13		145 × 63	12	215,0
159- 14	M16-18	154 × 70	6	260,0
159- 15		161 × 73	6	290,0
159- 16		168 × 76	6	400,0
159- 17	M20-22	177 × 80	6	430,0
159- 18		188 × 84	6	510,0
159- 19	M24-27	199 × 89	3	620,0
159- 20		200 × 90	3	650,0
159- 21		211 × 96	3	860,0
159- 22	M30	222 × 102	3	950,0
159- 24	M33	248 × 114	1	1250,0
159- 27	M36	277 × 127	1	1740,0
159- 30		315 × 142	1	2460,0
159- 32	M42	347 × 157	1	3080,0
159- 36	M48	391 × 176	1	4370,0

Stock-No.	mm	mm	g
159A- 1/16	46,5 × 15,5	48	1,0
159A- 5/64	52 × 18	48	2,0
159A- 3/32	58,5 × 20,5	48	4,0
159A- 7/64	66 × 23	24	5,0
159A- 1/8	66 × 23	24	5,0
159A- 9/64	69,5 × 25,5	24	8,0
159A- 5/32	74 × 29	24	10,0
159A- 3/16	85 × 33	24	18,0
159A- 7/32	91 × 36	24	21,0
159A- 1/4	96 × 38	24	30,0
159A- 9/32	102 × 41	24	43,0
159A- 5/16	108 × 44	12	59,0
159A- 11/32	114 × 47	12	79,0
159A- 3/8	122 × 50	12	103,0
159A- 7/16	129 × 53	12	131,0
159A- 1/2	145 × 63	12	215,0
159A- 9/16	154 × 70	6	260,0
159A- 5/8	168 × 76	6	400,0
159A- 3/4	199 × 89	3	620,0
159A- 7/8	222 × 102	3	950,0
159A- 1	277 × 127	1	1700,0

### 159S Hexagon Key Set



<b>Application</b>	for hexagon socket head cap screws according to DIN 912	
<b>Type</b>	in black plastic wallet	
<b>Material</b>	Chrome-Vanadium 59 CrMoV 4, Code No. 1.2243	
<b>Standard</b>	according to DIN 911/ISO 2936	

Stock-No.	Contents	mm	g
159S- 8M	1,5; 2; 2,5; 3; 4; 5; 6; 8 mm	12	135
159S- 10M	1,5; 2; 2,5; 3; 4; 5; 6; 8; 10; 12 mm	6	410
159S- 14M	1,5; 2; 2,5; 3; 4; 5; 6; 8; 10; 12; 14; 17; 19; 22 mm	1	2800

Stock-No.	Contents	mm	g
159S- 8A	1/16; 5/64; 3/32; 1/8; 5/32; 3/16; 7/32; 1/4 AF	12	96
159S- 10A	1/16; 5/64; 3/32; 1/8; 5/32; 3/16; 7/32; 1/4; 5/16; 3/8 AF	6	250
159S- 14A	1/16; 5/64; 3/32; 1/8; 5/32; 3/16; 7/32; 1/4; 5/16; 3/8; 1/2; 9/16; 5/8; 3/4 AF	1	1490

### 159SK Hexagon Key Set



<b>Application</b>	for hexagon socket head cap screws according to DIN 912	
<b>Type</b>	nickel plated, in plastic holder	
<b>Material</b>	Chrome-Vanadium 59 CrMoV 4, Code No. 1.2243	

Stock-No.	Contents	mm	g
159SK- 9M	1,5; 2; 2,5; 3; 4; 5; 6; 8; 10 mm	3	250
159SK-10M	1,5; 2; 2,5; 3; 4; 5; 6; 8; 10; 12 mm	3	415

### 159S-8P Hexagon Key Set



<b>Application</b>	for hexagon socket head cap screws according to DIN 912	
<b>Type</b>	in plastic storage box	
<b>Material</b>	Chrome-Vanadium 59 CrMoV 4, Code No. 1.2243	
<b>Standard</b>	according to DIN 911/ISO 2936	

Stock-No.	Contents	mm	g
159S- 8P	2; 2,5; 3; 4; 5; 6; 8; 10 mm	1	260

### 159SK Pocket Hexagon Key Set



<b>Application</b>	for hexagon socket head cap screws according to DIN 912	
<b>Type</b>	pocket-knife type holder, nickel plated	
<b>Material</b>	Chrome-Vanadium-Steel 59 CrMoV 4, Code-No. 1.2243	
<b>Standard</b>	according to DIN 911/ISO 2936	

Stock-No.	Contents	mm	g
159SK- 1	2,5; 3; 4; 5; 6; 8 mm	115	3 235
159SK- 2	2,5; 3; 4; 5; 6; 8; 10 mm	115	3 320
159SK- 3	1,5; 2; 2,5; 3; 4; 5; 6 mm	95	3 150
159SK- 4	3; 4; 5; 6; 8; 10 mm	115	3 360

Stock-No.	Contents	mm	g
159SK- 5	1/16; 5/64; 3/32; 1/8; 5/32; 3/16; 7/32 AF	95	3 165
159SK- 6	1/8; 5/32; 3/16; 7/32; 1/4; 5/16 AF	110	3 220
159SK- 7	3/16; 7/32; 1/4; 5/16; 3/8 AF	120	3 360
159SK- 8	3/32; 3/16; 7/32; 1/4; 5/16; 3/8 AF	120	3 370

### 159S-KK Pocket Hexagon Key Set



<b>Application</b>	for hexagon socket head cap screws according to DIN 912	
<b>Type</b>	in plastic holder with lever for easy raise of hexagon keys, blades nickel plated	
<b>Material</b>	Chrome-Vanadium 59 CrMoV 4, Code No. 1.2243	
<b>Standard</b>	according to DIN 911/ISO 2936	

Stock-No.	Contents	mm	g
159S-KK- 1	2,5; 3; 4; 5; 6; 8 mm	120	3 235
159S-KK- 2	2,5; 3; 4; 5; 6; 8; 10 mm	130	3 320
159S-KK- 3	1,5; 2; 2,5; 3; 4; 5; 6 mm	130	3 150
159S-KK- 4	3; 4; 5; 6; 8; 10 mm	120	3 360