

# MANUAL STACKER



- Compact & Powerful
- Easy to Operate
- Simple Design
- Built-in with Safety Valve
- QLS Function



Safety Valve



Quick Lifting System (unloaded)

## SPECIFICATIONS

MODEL	SH200-12	SH400-15	SH650-16	SH1000-16	SH1000-16L
Capacity	200 kg	400 kg	650 kg	1,000 kg	1,000 kg
Min. Height	90 mm	90 mm	95 mm	95 mm	95 mm
Max. Height	1,200 mm	1,500 mm	1,600 mm	1,600 mm	1,600 mm
Fork Length	500 mm	550 mm	650 mm	800 mm	1,100 mm
Fork Width	65 mm	75 mm	125 mm	125 mm	135 mm
Adjustable Fork Width	145 mm - 500 mm	165 mm - 520 mm	265 mm - 650 mm	265 mm - 600 mm	285 mm - 900 mm
Inner Straddle Width	380 mm	390 mm	420 mm	370 mm	660 mm
Outer Straddle Width	490 mm	500 mm	630 mm	580 mm	870 mm
Overall Height	1,530 mm	1,800 mm	1,950 mm	1,950 mm	1,950 mm
Overall Width	610 mm	620 mm	700 mm	650 mm	950 mm
Overall Length	950 mm	1,050 mm	1,300 mm	1,500 mm	1,800 mm
Net Weight	65 kg	105 kg	170 kg	230 kg	260 kg

\* All specifications are subject to change without prior notice.

# BATTERY STACKER



Battery Meter



Small Built-in Charger



Drive Unit-Optional for fully auto type



Soft-up Function (for SD1500-15 & SDW1000-25 only)

## FEEL THE DIFFERENCE

- Small Turning Radius
- Easy to Operate
- Low Maintenance Cost

## SPECIFICATIONS

MODEL	SD650-16	SD1000-16	SD1000-16L	SD1500-15	SDW1000-25
Capacity	650 kg	1,000 kg	1,000 kg	1,500 kg	1,000 kg
Min. Height	95 mm	95 mm	95 mm	95 mm	95 mm
Max. Height	1,600 mm	1,600 mm	1,600 mm	1,500 mm	2,500 mm
Fork Length	650 mm	800 mm	1,100 mm	850 mm	850 mm
Fork Width	125 mm	125 mm	135 mm	150 mm	125 mm
Adjustable Fork Width	265 mm - 650 mm	265 mm - 600 mm	285 mm - 900 mm	325 mm - 750 mm	275 mm - 725 mm
Inner Straddle Width	420 mm	370 mm	660 mm	490 mm	490 mm
Outer Straddle Width	630 mm	580 mm	870 mm	705 mm	705 mm
Overall Height	1,950 mm	1,950 mm	1,950 mm	2,050 mm	2,100 mm
Overall Width	700 mm	650 mm	950 mm	810 mm	780 mm
Overall Length	1,300 mm	1,500 mm	1,800 mm	1,650 mm	1,650 mm
Lifting Time	Approx. 17 sec	Approx. 25 sec	Approx. 25 sec	Approx. 30 sec	Approx. 30 sec
Battery Charger	Built-in Type AC 240V single phase				
Battery	DC 12V				
Net Weight	210 kg	270 kg	300 kg	470 kg	510 kg

\* All specifications are subject to change without prior notice.

# AUTO STACKER

## SPECIFICATIONS

MODEL	SA1000-16	SA1000-30	SA1500-30
Capacity	1,000 kg	1,000 kg	1,500 kg
Load Centre	600 mm		
Minimum Height	90 mm		
Maximum Height	1,600 mm	3,000 mm	3,000 mm
Fork Length	1,150 mm		
Fork Width	560 mm		
Overall Length	1,760 mm		
Overall Width	820 mm		
Overall Height	2,095 mm	2,035 mm	2,035 mm
Lifting Speed	150 mm/sc (Unloaded), 75 mm/sc (Loaded)		
Drive Speed	5.3 km/hr (Unloaded), 5 km/hr (Loaded)		
Load Wheel	78 mm P/U Tandem		
Drive Wheel	220 mm P/U		
Back Wheel	124 mm P/U		
Battery	DC 12V 120AH x 2		
Product Weight	520 kg	600 kg	600 kg

- Simple and Compact Design
- Easy to Control
- Small Turning Radius



\* All specifications are subject to change without prior notice

# RIDE-ON STACKER

- Easy to Control
- Excellent Stability
- Foldable Platform



## SPECIFICATIONS

MODEL	SR1000-16	SR1000-30	SR1500-30
Capacity	1,000 kg	1,000 kg	1,500 kg
Load Centre	600 mm		
Minimum Height	90 mm		
Maximum Height	1,600 mm	3,000 mm	3,000 mm
Fork Length	1,150 mm		
Fork Width	560 mm		
Overall Length	2,030 mm	2,060 mm	2,060 mm
Overall Width	780 mm		
Overall Height	2,050 mm	2,045 mm	2,045 mm
Lifting Speed	148 mm/sc (Unloaded), 58 mm/sc (Loaded)		
Drive Speed	5.3 km/hr (Unloaded), 5 km/hr (Loaded)		
Load Wheel	78 mm P/U Tandem		
Drive Wheel	230 mm P/U		
Back Wheel	124 mm P/U		
Battery	DC 24V / 210AH		
Product Weight	650 kg	930 kg	1090 kg

\* All specifications are subject to change without prior notice

# RIDE-ON STACKER (With Counter Balance)

- Easy to Control
- Excellent Stability
- Foldable Platform



**SCB1200-30**

## SPECIFICATIONS

MODEL	SCB1200-30
Capacity	1,200 kg
Load Centre	500 mm
Minimum Height	70 mm
Maximum Height	3,000 mm
Fork Length	1,070 mm
Fork Width	Adjustable from 200 mm - 910 mm
Overall Length	2,640 mm
Overall Width	850 mm
Overall Height	2,040 mm
Lifting Speed	147 mm/sc (Unloaded), 108 mm/sc (Loaded)
Drive Speed	5.3 km/hr (Unloaded), 5 km/hr (Loaded)
Load Wheel	210 mm P/U
Drive Wheel	230 mm P/U
Back Wheel	124 mm P/U
Battery	DC 24V / 210 AH
Product Weight	1,830 kg

\* All specifications are subject to change without prior notice