

AERIAL WORK PLATFORM

SINGLE MAST AERIAL WORK PLATFORM

- **Stable and Reliable**



Safety Electrical Features

Ergonomic ground control panel, power display, electric leakage protection, circuit breaker etc.

CE certified stabilizers and electric safety switch elements from the inter-lock for platform ascending and descending



DOUBLE MAST AERIAL WORK PLATFORM

- **Simple and Convenient**



Double protection with supporting bolts and evolvable stabilizers to minimize the blind area of aerial work platform usage.



SPECIFICATIONS

MODEL	Max. Platform Height (m)	Max. Working Height (m)	Capacity (kg)	Number Of Person Permitted On The Platform	Platform Size (mm)	Outrigger Footprint (mm)	Voltage (V/Hz)	Motor Rating Lifting (KW)	Stored Dimensions (mm) L x W x H	Machine Weight (kg)
GTWY6-1006	6	7.7	160	1	630 x 650	2,060 x 1,900	AC220/50	0.75	1,290 x 880 x 1,740	390
GTWY8-1008	8	9.7	136	1	630 x 650	2,300 x 2,180	AC220/50	0.75	1,290 x 880 x 2,080	420
GTWY10-1010	10	11.7	120	1	630 x 650	2,400 x 2,280	AC220/50	0.75	1,390 x 880 x 2,160	480
GTWY8-2008	8	9.7	300	2	1,200 x 600	2,020 x 2,000	AC220/50	0.75	1,390 x 880 x 1,860	610
GTWY10-2010	10	11.7	300	2	1,200 x 600	2,340 x 2,220	AC220/50	0.75	1,390 x 880 x 2,060	680
GTWY12-2012	12	13.7	250	2	1,330 x 600	2,560 x 2,460	AC220/50	1.5	1,590 x 1,020 x 2,440	810
GTWY14-4214	14	15.7	200	1	1,480 x 860	3,350 x 3,000	AC220/50	0.75 / 1.5	2,360 x 1,250 x 1,920	1,950
GTWY16-4216	16	17.7	136	1	700 x 700	4,100 x 3,000	AC220/50	0.75 / 1.5	3,120 x 1,250 x 2,190	2,100
GTWY18-4218	18	19.7	136	1	700 x 700	4,100 x 3,140	AC220/50	0.75 / 1.5	3,120 x 1,390 x 2,350	2,200

* The above models are available in either AC or DC type or dual operation.

* All specifications are subject to change without prior notice.

ORDER PICKER

**SPEED UP
YOUR JOB!**



Foldable Platform

SPECIFICATIONS

MODEL	Max. Platform Height (m)	Max. Working Height (m)	Capacity (kg)	Number Of Person Allowed	Platform Size (mm)	Cargo Platform Size (mm)		Power Supply (Volt)	Power Input (kw)	Stored Dimension L x W x H (mm)	Machine Weight (kg)
						Closed	Opened				
GTWY2.8	2.8	4.5	200	1	600 x 405	600 x 620	1175 x 620	DC 12	0.7	1,430 x 880 x 1,750	410
GTWY3.3	3.3	5.0	200	1						1,430 x 880 x 2,060	430
GTWY3.8	3.8	5.5	200	1						1,430 x 880 x 1,750	450
GTWY4.3	4.3	6.0	200	1						1,430 x 880 x 2,060	490

* All specifications are subject to change without prior notice.

OPTIONAL



Self Propelled



Slideable Platform



Staircase Type



On-Truck Mounted



Towing Type