



DRUM PUMPS - TRANSFER OILS / CHEMICALS / FUELS

DRIVE - ELECTRIC AC 220 VOLTS / AC 220 VOLTS EX-PROOF / PNEUMATIC / DC 12 VOLTS

MATERIAL - SS-304 / ALUMINIUM

PUMP FEATURES	SB-6-SS	SB-3-SS-EX	SZQ-40-SS	ETP-40-DC	LB-70-DC
PORTABLE LIGHT WEIGHT SMALL SIZE					
APPLICATIONS DIESEL OIL ENGINE OIL VEGETABLE OIL HYDRAULIC OIL LUBRICANTS ALCOHOL ALKALIS LIGHT CHEMICALS					
VISCOSITY MAX 320 CENTIPOISE 1500 SSU					
TEMPERATURE & S.G. 80° CELSIUS 1 to 1.4					
SPECIFICATIONS	AC 220 V	AC 220 V Ex-Proof	PNEUMATIC	DC 12 V	DC 12 V
MODEL	SB-6-SS	SB-6-SS	SZQ-40-SS	ETP-40-SS / AL	LB-70-SS / AL
MOTOR POWER	0.55 kW (0.75 Hp)	0.88 kW (1.2 Hp)	VACUUM SUCTION	180 Watts	380 Watts
MOTOR SPEED	8000 Rpm	12000 Rpm	-	-	10000 Rpm
VOLTAGE	220 Volts	220 Volts	-	12 Volts	12 Volts
PHASE	Single	Single	-	-	-
FREQUENCY	50 Hz	50 Hz	-	-	-
CURRENT	2.5 A	4 A	-	-	-
CAPACITY - MAX	100 Lpm	130-150 Lpm	80 Lpm	40 Lpm	100 Lpm
HEAD - MAX	7.5 Mtr	7.5 Mtr	10 Mtr	4 Mtr	5 Mtr
INPUT SIZE	40 mm	50 mm	40 mm	42 mm	42 mm
OUTPUT SIZE	32 mm	32 mm	40 mm	25 mm	25 mm
PUMP TUBE	SS-304	SS-304	SS-304	SS-304 / ALU	SS-304 / ALU
IMPELLER	SS-304	SS-304	SS-304	SS-304 / PP	SS-304 / PP
OUTLET END	SS-304	SS-304	SS-304	SS-304 / ALU	SS-304 / ALU