

Product Data Sheet



Lithium Metallic Grease 800

Application: An Excellent Choice for High Speed Bearings applications. Recommended for the Lubrication of Automotive Parts such as Chassis Points, CV-Joints, Gears, Roller and Bearing applications.

Performance Benefits:

- ✓ Reduces Friction and Pressure
- ✓ High-Temperature (Non-Melt Technology)
- ✓ Extend Bearing Life
- ✓ Increase Lubrication Intervals
- ✓ Prevent Seizure
- ✓ Extreme Pressure Stability
- ✓ Anti Rust Characteristics
- ✓ Multi Purpose Applications

Characteristics & Performances

Properties	Methods	Type
NLGI Grade		2-3
Texture	Visual	Smooth
Color	Visual	Red/Blue
Additive	Liquid	Lithium
Base Oil Color		White Oil
Base Oil viscosity at 40°C, mm/s (cSt)	ASTM D 445	100
Flash Point	ASTM D 92-05a	> 280
Dropping Point, °F	ASTM D 566-02	> 700
Salt Spray Test (hours)	ASTM B 117	> 250
Dry film thickness = 30um		

The above values are representative of a current production. They are not representative of specifications.

Packaging: Available in 500g (Can), 16kg (Pail) and 200 kg net weight drums.

Storage: The product should not be stored longer than 12 months. The recommended storage temperature shall be between 0°C and 35°C.

Handling: Carefully review the Material Safety Data Sheet for handling.

DEPTAMBEN RI
NPT NO: DQ066G2NNN310118