

TOSHIBA

Leading Innovation >>>

e-STUDIO2802A

e-STUDIO2802AM

e-STUDIO2802AF

Small footprint,
big results.



COPY



PRINT



A3



DUPLEX




COLOUR
SCAN



28
BW CPM
COPY
SPEED

TOGETHER
INFORMATION

A3 and A4 Monochrome copy-based MFP



A compact machine which supports not only A4 paper, but also prints on A3 paper using paper feed from the bypass tray.


Ease of Use



Intuitive and efficient 4-line LCD info panel and special feature buttons which support ID Card Copy & Original Mode selection.

High Image Quality



Outstanding reproduction of grey shades. The Background Erase mode removes background colours when copying originals.



Background Erase

Reduced Cost

Reduced paper and print cost using 2-in-1/4-in-1 function.



SPECIFICATION for	e-STUDIO2802A	e-STUDIO2802AM	e-STUDIO2802AF
GENERAL			
Copying/Printing Process	Indirect electrostatic photographic method		
Print & Copy Speed	28cpm		
Warm-up Time	Approx. 18 seconds		
Paper Size & Weight	Drawer: A4 (64 - 80gsm) Stack Feed Bypass: A3 / A5-R (52 - 216gsm)		
Paper Capacity	Drawer: 250 sheets Stack Feed Bypass: 50 sheets		
Max. Paper Capacity	300 sheets		
Paper Exit	Face down/Inner exit (50 sheets)		
Processor	Cortex A8 500MHz		
Memory	512MB		
Dimensions	W390 x D540 x H402 (mm)	W390 x D540 x H505 (mm)	
Weight (Approx.)	21.5kg	26.5kg	28.5kg
Power Consumption	1.4kW (220-240V)		
Operation Noise	64.75dB[A]		
Special Features	Auto Sleep Mode, Auto Energy Saver		
COPY			
Max. Original Size	A4	A4 (Via Platen) A3 (Via RADF)	
Resolution	2400dpi x 600dpi (with smoothing)		
Multiple Copy Qty	1-999		
First Copy	Less than 6.4 seconds (A4 size from 1st drawer, 100%)		
Zoom	25% to 400% (1% Increment)		
Copy Mode	Text, Text/Photo (Default), Photo, Background Erase		
Image Density Control	Automatic / Manual (9 Steps)		
PRINT			
Resolution	2400dpi x 600dpi (with smoothing)		
Page Description Language	PCL6 (PCL_XL), PCL5e, PCL5c		
Operating Systems	Windows Vista SP2 (32/64 bit) Windows 7 SP1 (32/64 bit) (SP1 Recommended) Windows 8/8.1 (32/64 bit) Windows Server 2008 SP2 (32/64 bit) Windows Server 2008 R2 SP1 (64 bit) Windows Server 2012/R2 (64 bit) Mac OS 10.6, 10.7, 10.8, 10.9, 10.10 UNIX, Linux (CUPS)		
Interface	Standard: 10/100 BaseT, USB 2.0/Hi Speed		
Network Protocol	TCP/IP (IP v4/IP v6) NetBIOS over TCP/IP		
Print Protocol	LPR/LPD, Port 9100 (bi-directional), IPP ver1.1		
Print Function	Toner Save Mode, Watermark, Multiple Pages Per Sheet		
SCAN			
Resolution	600 x 600dpi		
Scan Speed	Up to 25spm		
Scan Modes	B&W, Greyscale, Colour		
File Formats	B&W: TIFF-Multi/Single page, PDF-Multi/Single-Page Greyscale: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page		
Scan Agent	Scan to USB, Remote TWAIN, Scan to File (SMB/FTP), Scan to Email		
FAX (OPTION)			
Compatibility	N.A		Super G3, G3
Data Compression Method	N.A		JBIG, MMR, MR, MH
Modem Speed	N.A		33.6kbps - 2.4Kbps (Auto Fallback)
Transmission Speed	N.A		Approx. 3 sec.
Broadcast Transmission	N.A		Max. 32 Groups, 220 destinations per job
OPTIONS			
Wireless LAN Module	GN-1080	✓	
Harness Kit for Coin Controller	GQ-1131	✓	
Front Cover Customisation Kit	KK-2505	✓	
Desk	MH-2505	✓	

TSP Version 1.0

Distributed by

Microsoft and Windows® are registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand and/or product names are trademarks of their respective owners. This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. 1GB is equivalent to 1 billion bytes. Warm-up time and print speed may vary depending on the operating environment. ©2015 TOSHIBA TEC CORPORATION All rights reserved. As an ENERGY STAR Partner TOSHIBA TEC CORPORATION has determined that this multifunctional device model meets the ENERGY STAR guidelines for energy efficiency.

Driven by

