

Rubber Petrol & Oil Suction & Delivery Hose (A430)



Application:	Specially designed for use on hydraulic systems such as oil return hose; can also be used for suction and discharge of various petroleum products with maximum 30% aromatic content. Used for wet exhaust applications.
Tube:	Black, nitrile
Cover:	Black, smooth (wrapped finish), synthetic rubber, abrasion, weather and oil mist resistant
Temperature:	-20°C to 70°C
Reinforcement:	High strength synthetic cord plus wire helix and anti-static copper wire

Part No.	Dimensions (mm)		Working Pressure		BP PSI	Bend Radius (mm)	Weight kg/mtr	Vacuum (m.H2O)	Coil Lengths
	ID	OD	PSI	MPa					
A430020	19	30	145	1	435	80	0.69	9	20, 60
A430022	22	32	145	1	435	90	0.80	9	20, 60
A430025	25	35	145	1	435	105	0.87	9	20, 60
A430032	32	43	145	1	435	135	1.12	9	20, 60
A430035	35	46.5	145	1	435	150	1.21	9	20, 60
A430040	38	49.5	145	1	435	165	1.42	9	20, 60
A430042	42	54	145	1	435	195	1.50	9	20, 60
A430045	45	57	145	1	435	205	1.60	9	20, 60
A430048	48	62	145	1	435	215	1.72	9	20, 60
A430050	51	63	145	1	435	230	1.87	9	20, 60
A430055	55	68	145	1	435	250	2.05	9	20, 60
A430060	60	73	145	1	435	275	2.48	9	20, 60
A430065	63	78	145	1	435	290	3.15	9	20, 60
A430070	70	83	145	1	435	330	3.48	9	20, 60
A430080	76	89	145	1	435	360	3.85	9	20, 60
A430090	90	105	145	1	435	440	4.22	9	20, 60
A430100	102	118	145	1	435	515	5.30	9	20, 60